STATE OF AI REPORT.

October 8, 2026

Nathan Benaich

AIR STREET CAPITAL.

About the author

Nathan Benaich

General Partner of **Air Street Capital**, investing in AI-first companies.

nathan@airstreet.com

Welcome to the 9th annual State of AI Report

- Analyzing the last 12 months of AI research, industry, politics, safety and predictions.
- Independently crafted every year since 2018.
- Informs conversation around AI today and its implications for the future.
- Freely available at **www.stateof.ai**
- Peer reviewed by members of top AI labs, startups, policy and academia.

What you need to know from the 2026 State of AI Report

Research

- Anthropic, OpenAI, and Google lead as benchmarks saturate. Better post-training, data, evaluations, and scaffolding expand agent capabilities.
- AI accelerates AI development: Claude led 26% of Anthropic's measured model R&D under supervision. Choosing worthwhile experiments is the next frontier.
- Physical AI approaches its GPT-2 moment, open mathematics problems fall, and AI-assisted drug programs reach Phase 3 as data and model licensing grows.

Industry

- Agent use and monetization broadens beyond developers. A Genius Bar for AI could help more people extract value through better tools and setup.
- OpenAI and Anthropic report combined annualized revenue run rates of roughly $105B across their businesses and inference business skyrockets.
- The SaaSpocalypse exposes uncertain winners. Financing, power, and construction constrain supply, while our data-center NIMBYism prediction plays out.

Politics

- US model export restrictions make access conditional. The superintelligence agenda and Pentagon dispute sharpen the fight over AI control.
- Selected sovereign AI pledges total about $138B as countries realise they cannot rent sovereignty. Many will have to bargain for access to the frontier.
- Frontier-lab leaders call for slower capability gains, with no agreement on who can require pauses, authorize restarts, and verify compliance.

Safety

- During reduced-safeguard evaluations, OpenAI agents attacked Hugging Face while trying to cheat their scorer.
- Anthropic documents misuse in cyberattacks, surveillance, scams, and weapons development.
- Frontier attacks require frontier defense. Guardrails blocked Hugging Face's forensics, leading it to use a Chinese open-weight model.
- Reasoning-only monitors missed sabotage in tests. Values training cut fictional blackmail from 65% to 19%, with production reliability unproven.

Section 1: Research

12 months pass, and the frontier fight is now a three-lab race

On Artificial Analysis's Intelligence Index, Claude Opus 5.5 leads at 58, and GPT-6 Astra and Google's Gemini 4 Argon tie at 53. On Arena's default ranking, built from people's votes, Argon leads at 1525, a tight pack of Claude models follows at about 1505 and OpenAI's best, GPT-5.6 Sol, ranks #20. China's best open-weights model, Xiaomi's MiMo-V2.6-Pro, scores 46 on the index. Argon is so far only available to selected users.

Intelligence Index, best model per lab



Arena default view, best model per lab



Chinese open-weight models overtook American ones in AI research papers in 2026

We analyzed AI papers on arXiv mentioning 21 model families. While closed US models (GPT, Claude, Gemini) account for 42% of mentions in 2026, they are losing ground to Chinese models. Zeta Alpha analysis reveals that among open-weight models, Chinese families surged from 9% of mentions in 2024 to 31%, US models fell from 31% to 23%, and Qwen overtook Llama.

All models: share of mentions by region (%)



Open-weight models only (%)



Qwen vs Llama (%)



Same model, better harness = stronger agent

With each model fixed, changing the harness delivered a 6x gain on SWE-Bench Mobile, while Meta-Harness raised Haiku 4.5 from 27.5% with Claude Code to 37.6% on TerminalBench-2. Meaningful model comparisons require disclosing the harness and holding it fixed or varying it systematically.

- On WeaveBench, LongHorizon-Harness improves Qwen 3.7-Plus enough to exceed the baseline performance of Opus 4.7.
- A controlled test paired three models with three harnesses on 100 SWE-bench Verified tasks. GLM-5.1 rose from 52.5% to 65.5% between the minimal and full harnesses. Harness-induced performance variance was 7.8x model-induced variance in this experiment.



Agents improve by choosing among specialized harnesses

A single harness can work well on average yet miss tasks that need a different approach. Researchers at Meta, Duke and UC Davis evolve two harnesses on different development tasks, then choose one for each new problem. With the execution model held fixed, this improves held-out math and coding results over Meta-Harness.

- With Gemini 3 Flash, the branches share 47% coverage, but each solves some problems the other misses.
- The router reaches 62% on Gemini math versus Meta-Harness's 46%, below the branches' combined potential coverage of 67%.
- Coding also improves: Terminal-Bench 2.0 rises from 44.8% to 50.0%, and SWE-bench Lite from 63.6% to 66.0%, with Sonnet 4.5 fixed.

Different problems solved by each branch



Figure 2(b), math panels. 200 tasks per model. Circle areas are schematic.

Recursive language models treat prompts as parts of the environment

Long inputs can overwhelm a model even before they fill its context window. MIT's Recursive Language Models (RLMs) keep the input in a code workspace, where the model can inspect it and delegate pieces to further (recursive) model calls. This lets a fixed model work through inputs too large to read in one pass.

- The authors trained Qwen3-30B-A3B with RL on short tasks and found transfer to much longer inputs and new domains sharing a decomposition strategy.
- The authors explain this as turning unfamiliar tasks into familiar subproblems: each model call stays "locally in-distribution" with its training.
- Transfer depends on learning a reusable decomposition, and RLMs are not uniformly cheaper. Recursive calls use fixed weights at inference.



Skills and memory let agents reuse know-how without retraining

Skills package reusable instructions and code, while memory preserves information for later tasks. These let developers improve an agent between model releases by changing what it can reuse. Papers matching the broad skills query rose from 152 to 1,486 in January-August 2025 and 2026.

Skills paper matches, Jan-Aug 2025 vs 2026



Memory tool matches, Jan-Aug 2026



Karpathy's autoresearch popularized the rush to recursive self-improvement (RSI)

RSI is the pursuit of AI that builds better AI, autonomously. In March, Andrej Karpathy released autoresearch, a project in which an agent edits the training code of a small nanochat model, trains for a fixed five minutes, keeps what improves, and repeats roughly 100 times overnight on one GPU. The user edits program.md, the instructions that define the research org. As Karpathy put it: "This repo is the story of how it all began."

- The repo reached roughly 95,000 GitHub stars and 13,400 forks in 5 months.
- A fixed 5-minute training budget makes every experiment comparable and turns one GPU into roughly 100 experiments a night, scored on validation bits per byte.



We're seeing a rapid growth in self-improvement papers

Papers matching verifiable rewards grew 10.4x in January-August 2026 versus the same months of 2025, compared with 2.7x for RSI. The practical opportunity is to automate experiments with reliable scoring. Choosing valuable research questions remains a separate (and very valuable) problem...

Growth in paper matches, Jan-Aug 2026 / 2025



Narrow RSI query: 2.7x



Agents can improve their own scaffolds, but acceleration is unproven

Darwin Gödel Machine rewrites an agent's scaffold: the prompts, tools and workflow around a frozen model. Hyperagents also rewrite the procedure that makes those edits. This can automate more of agent engineering, but a better agent does not necessarily become a better inventor of future agents...yet!

- Huxley-Gödel Machine selects agents by their descendants' scores. With GPT-5, it fixed 57.0% of SWE-bench Lite issues vs. SWE-agent's 56.7%.
- Red Queen co-evolves agents and evaluators. Its paper acceptance rate rose to 38.8% vs. HGM-H's 21.8% at matched search cost, as rated by AI judges.
- Weco reports beating its hand-tuned agent in 100 trials. Using the new agent to improve further agents gave no significant efficiency gain, however.

Making the improvement procedure editable



Stronger models can outgrow their harnesses

Many harnesses have included elaborate behavioral rules, reminders and planning mechanisms to compensate for old model limitations. However, as models become more capable and successful agent behavior is trained back into them, these workarounds become redundant and can even hobble stronger models. Harnesses should provide interfaces that make the environment easier to act on, without adding redundancy in model behavior.

- Claude Code removed 80% of the system prompt for advanced models, with no measurable loss on coding evaluations. Few-shot tool use examples are also found to reduce exploration, with good interface design being more important.
- Harnesses have become curricula, where trajectories produced inside an evolving harness can update model weights (see Continual Harness). Recent GPT models are trained on the codex harness.
- Performance between lightweight and sophisticated harnesses shrink as model capability improves: the durable harness investments that remain are environment interfaces (tools, MCP servers), state management, observability and agent infrastructure (sandboxes, runtimes, etc).

Agents approach official instruct scores on PostTrainBench's revised evaluation

PostTrainBench tests autonomous post-training: each run targets one small base model and one benchmark, with 10 hours on one H100. Version 1.2 covers four base models and six benchmarks. Results measure task-specific optimization; the official instruct models are reference points trained with different resources.

- On v1.2, Fable 5.1 scores 44.6%, Opus 5.5 43.8% and GPT-6 Astra 41.9%, versus 48.4% for official instruct models.
- BFCL was removed after task-quality and item-targeted training concerns. The former 95% result is insufficient evidence of general function-calling superiority.
- These are benchmark-specific model adaptations, not one broadly improved assistant. Five Fable 5.1 GPQA runs used Opus 5 as a fallback.



Frontier agents sustain multi-day research with limited novelty in a speedrun

Prime Intellect tested 18 models in 153 runs on the nanoGPT optimizer speedrun: train a 124M-parameter GPT to a target loss of 3.28 in fewer steps. Runs used 8xH200 GPUs without internet. Fable 5's best trajectory lasted 8.7 days, with limited novelty reported in this setting.

- Fable 5 reached 2,726 steps from a 3,290-step baseline, closing 81.7% of the gap to a 2,600-step human record claim.
- Research budgets differed: after 24 hours, Fable 5 had reached 3,010 steps, versus 3,045 for Opus 5.
- Strong agents re-tested borderline results across seeds and revisited earlier failures, but limited novelty here does not establish a general limit on AI research.



Can agents produce a top-tier research paper? No, but they can do its engineering.

Researchers introduced shadow evaluations, in which they give an agent the central research question of a high-quality unpublished NeurIPS submission (so contamination is impossible) and let the paper's original authors grade the output as reviewers. Each agent got six days, $3,000 of API credit, GPUs and the open web.

- Opus 4.8 completed all the engineering without human help, but both its papers were scored 2/6 and 1/6 - unambiguous rejections.
- Five failure modes recurred: no sense of the publishable bar, uncreative fixes, ineffective backtracking, poor resource awareness and instruction drift.
- Both runs ended with under half the API budget spent, despite the models knowing their usage in real-time.
- Self-review by agents never returned an acceptance in dozens of rounds and the issues it flagged were often the same ones the human reviewers later raised.

Table 1 Summary of the original paper authors' reviews of the agents' submitted work. Section 3 contains additional details on our setup and Appendix A outlines the research questions and relevant context for both papers.

Criterion	Paper 1 (Personas)	Paper 2 (TabPFN)	Summary of expert comments
Quality	●●○○ 2/4	●○○○ 1/4	Unprincipled data and experiment choices; conclusions did not follow from the evidence.
Clarity	●○○○ 1/4	●●○○ 2/4	Dense, unclear writing; hard to tell what matters.
Significance	●●○○ 2/4	●●○○ 2/4	Of limited interest; not well justified over prior and comparable work.
Originality	●●●○ 3/4	●●○○ 2/4	New datasets and some new methods, but built primarily on prior work.
Overall	●●○○○○ 2/6	●○○○○○ 1/6	Both unambiguous rejections.
Confidence	●●●●○ 4/5	●●●●● 5/5	Both reviewers were confident or certain in their assessments.

The work of smarter models is increasingly accepted by lab's staff

- **In an essay on building RSI, Anthropic (left chart) shared data on the code contributions of their employees. The output has increased by 8x in Q2 2026 compared to pre-2025, corresponding with the use of Mythos Preview. OpenAI sees the same results too (right chart).**





...and starts suggesting where the research should go next

- **Even more interestingly, researchers rated next-direction turns suggested by Mythos Preview as better than the route a human researcher picked 64% of the time. This suggests that frontier models are generating quality contributions that exhibit research taste.**



Claude now leads a quarter of Anthropic's model R&D, with humans supervising

Anthropic's internal automation index tracks how much responsibility Claude takes on across model R&D. The share rated "AI leads" rose from under 1% in February to 26% in August 2026: Claude completes most of a task from a high-level prompt while a human supervises. More than 90% of measured work now involves substantial AI collaboration or leadership, but none is fully autonomous yet.



Within 6 months, OpenAI researchers are solving much longer tasks autonomously

In January 2026, OpenAI researchers used AI agents to autonomously complete tasks normally requiring 4-8 hours of human labor with an 18% success rate. By July 2026, that same 18% success rate was achieved on significantly more complex tasks requiring 32-64 hours of human labor.





But coding agents are mostly used post-experimental ideation and design

So far, the majority of coding agent use in OpenAI internal research has been on execution-related workflows, namely working on research infrastructure code, launching, monitoring and debugging runs, and technical help and review. Deciding what to research and how to do it is still not solved by coding agents.



As task benchmarks saturate, RSI evidence is moving inside the labs

Public AI R&D suites no longer rule out advanced capabilities once models pass their thresholds or exploit their scoring. Labs increasingly rely on internal evidence of research acceleration. RSI-Exam tests 88 tasks externally, but no model reaches its frontier-calibrated reference.

- METR's Opus 5.5 review cites a preliminary estimate of ~1.5x AI-driven research acceleration. The estimated time period is unspecified.
- OpenAI reports 3.1 agent-workdays per human workday. This measures activity, not an equivalent gain in research output.
- Noam Brown estimates about a 3x speedup, limited by serial experiments and GPU supply.

RSI-Exam: 88 tasks



Less shooting in the dark as more of the pretraining recipe got written down

Detailed technical reports, codebases and training logs make building capable models less opaque than three years ago. More of the path from pretraining to reasoning and agentic behavior is now public. But scaling-law guidance is still incomplete, and choosing the right data mix remains experimental. Training a strong model still takes research judgment (the infamous "taste") as well as enough compute to test many ideas.

- Training becomes more selective: Nemotron 3 Super uses 20T tokens for broad coverage, then 5T emphasizing quality. Step 3.5 Flash later emphasizes code, reasoning and tool use, retaining some general data as it specializes.
- Longer context can weaken other skills. After math scores dipped during million-token training, NVIDIA added a phase alternating 1M-token and 4K-token sequences to mitigate the decline.
- Healthy training loss can hide failing components. StepFun found MoE experts becoming inactive or developing extreme internal values while aggregate metrics looked normal. Monitoring individual experts exposed these problems.

The RL recipe got written down too

Several well-documented open reproductions of agentic training pipelines were published this year, achieving results close to the state of the art. While open agent model reproductions remain a few steps behind the frontier, the tricks they disclose lower the barrier for a new lab to start successfully training an agent, with Thinking Machines and OpenThoughts Agent being good examples.

- Meta's ScaleRL reports 400k+ GPU hours of ablations covering precision fixes (fp32 logits), RL objectives and batch size. Many findings reverse conclusions from smaller scales.
- Cursor's Composer 2 technical report includes many long-horizon rollout details such as updating behaviour policy weights mid-rollout, and fixes for sampler/trainer inconsistency such as MoE router replay.
- DeepSeekMath-v2 shares their agentic data-generation pipeline in detail. Kimi K3 details ways to train reasoning efforts, compatibility with multiple harnesses, and anti-reward-hacking machinery.



Scaling agentic RL creates huge demand for CPUs and memory alongside GPUs

Long-horizon agentic RL spends much of its compute on inference (rollouts) rather than backprop, runs stateful rollouts against realistic often sandboxed environments, and must continuously sync fresh weights into distributed inference fleets without letting trajectories go stale.

- Inference dominates RL compute: MAI-Thinking-1, a 1T-A35B MoE, uses 4,096 of 4,864 GB200s for inference, roughly five times its learner allocation, with generations up to 128k tokens.
- CPU and memory demand rises too: Kimi K3 used 51.2M stateful sandboxes with pause/resume, fork, snapshot, and sub-second launch. DeepSeek's DSec reports 30,000 CPU cores and 250 TB of RAM serving 3M sandbox instances daily in one deployment unit. Yet ~90% of sandboxes average ⩽5% of requested CPU capacity, making resource sharing and idle-memory reclamation essential.
- Training environments increasingly resemble real work: Kimi K3 combines mocks of Gmail, Notion, Slack, and Canvas with harnesses including Kimi Code, Claude Code, and Codex.
- Inference can be distributed: Composer 2 synchronizes weights every training step through S3. Delta compression reduces updates for a 1T-parameter model to a few GB, enabling geographically distributed RL inference.

The training gym gets harder as the agent gets better

RL agents learn little from tasks they always pass or always fail. Microsoft's TaskPilot generates coding problems and hidden tests in real repositories, then revises their difficulty using the current model's attempts. As FrogNano improves, new task batches keep its training near the edge of what it can solve.

- Agent-World generated 1,978 environments and 19.8k tools to train 8B and 14B agents, improving tool use, planning and coding across 23 benchmarks.
- FrogNano combines a simpler tool interface with five batches totaling 1.5k tasks. Qwen3.5-4B solves 61.5% of SWE-bench Verified (validation) and 37.6% of held-out SWE-bench Pro issues.
- Checks still matter, of course. With GPT-5.2 fixed, Universal Verifier falsely accepted 1% of failed computer-use runs, vs. 7% for WebJudge and 10% for WebVoyager.

Computer-use false positives (internal set)



Models can learn from stronger teachers, specialists, or themselves

Distillation teaches a student to imitate a teacher. Off-policy uses teacher or earlier-model responses, while on-policy uses the current student's attempts. Self-distillation means the teacher is a copy of the same model.

- **Cheaper transfer:** Alibaba compared two methods from the same Qwen3-8B checkpoint. On-policy distillation reached 74.4% on AIME24 using 1.8k GPU-hours. By contrast, RL needed 17.9k GPU-hours to reach 67.6%.
- **Combining specialists:** Xiaomi trains math, coding and instruction-following teachers separately to avoid interference, then combines their skills via Multi-Teacher On-Policy Distillation (MOPD).
- **Learning from itself:** Self-Distilled Reasoner gives a frozen copy the worked solution. It guides the student token by token on the student's own attempt, so no larger teacher is required.

How on-policy self-distillation works



Prefix = attempt so far. Same starting checkpoint. Teacher probabilities are not correctness scores.

Frontier labs' own cheaper models decoded the reasoning they tried to hide

Labs hide their models' reasoning because rivals can train on it using a process called distillation. Panfilov and colleagues found that cheaper models could reveal stronger models' hidden reasoning. Providers patched the flaw. Could restricting access to these traces widen the gap between open-weight and closed models?

- Given Opus 4.8's encrypted reasoning block, Haiku 4.5 wrote out the reasoning in plain text. The same attack worked at OpenAI and Google.
- A reasoning trace shows the teacher's steps, not just its answer. In prior work, reconstructed traces lifted a 7B student from 68.4% to 76.0% on MATH500.
- Closing this extraction route could make frontier reasoning harder to obtain for training. The paper does not establish how much recent open-model progress depended on it, or whether the capability gap will widen - we suspect it could.

How hidden reasoning was exposed

1. Opus 4.8 generates reasoning
API returns an encrypted reasoning block.

↓

2. Replay the block to Haiku 4.5
The same provider accepts Opus's block.

↓

3. Haiku reveals the hidden reasoning
A prompt induces it to write the trace as plain text.

Self-play can learn from documents or from programs it invents

Self-play creates its own training tasks, so is an appealing approach to AI training. SPICE post-trains a reasoner on document-grounded questions, whereas zero-data self-play learns from programs, starting from random weights. Natural text/DNA validation selects hyperparameters but supplies no pretraining gradients.

SPICE: document-grounded post-training



Qwen3-4B-Base: 35.8%→44.9% overall (+9.1 pp) across 11 reasoning benchmarks. R-Zero: 39.5%; Absolute Zero: 40.7% under the same evaluation.

Zero-data self-play: synthetic pretraining



≈100% exact-match on reverse-string, stack and associative recall after sufficient in-context examples; no weight updates at evaluation.

Models can learn while searching for a better solution too

AlphaEvolve searches for solutions using a frozen model. TTT-Discover, meanwhile, updates gpt-oss-120b's weights during inference time, rewarding promising attempts and reusing the best candidates. The goal is one better solution to the current problem, rather than a model that generalizes to new tasks.

- TTT-Discover improved two mathematical bounds. TriMul runtime fell 51.5% on A100 (4,531→2,198 µs) and 15.3% on H100 (1,371→1,161 µs), versus the best human entries.
- Reusing promising candidates mattered more than weight updates in one ablation. An attention kernel and a third math problem missed the leaders.
- TTPO trains on majority-vote answers. Across three math benchmarks, Qwen3-1.7B rose from 38.0% to 45.2% without supplied answer labels.

Selected results; H100 TriMul search below

	Mathematics Erdős' Min. Overlap (↓)	Kernel Eng. (TriMul) A100 (↓)	Kernel Eng. (TriMul) H100 (↓)	Algorithms (AtCoder) Heuristic Contest 39 (↑)	Biology Denoising (↑)
Best Human	0.380927 [20]	4531 µs	1371 µs	566,997 [56]	0.64
Prev. Best AI	0.380924 [30]	N/A	N/A	558,026 [37]	N/A
TTT-Discover	0.380876	2198 µs	1161 µs	567,062	0.71



What happens in context no longer has to stay in context

Experience gathered within a trajectory changes a sequence model's token distribution. This experience is expensive to keep in context and disappears when the context is cleared. New continual learning approaches consolidate useful behaviours learned in-context into persistent memory or model updates, allowing experience from one trajectory to improve behaviour on the next.

- **Monash / ByteDance Seed:** Experience Distillation retains at least 64.8% of in-context learning gains, versus 3.8% for direct SFT on the same experience. Across 749 software engineering tasks and six text adventure games, it matches RL baselines with at least 9.6x fewer environment interactions.
- **Microsoft Research:** Online Experiential Learning extracts reusable lessons and consolidates them into model weights over successive rounds. On Frozen Lake, Qwen3-1.7B reduces average response length to roughly 70% of its initial level by round three, alongside improved accuracy. Separate tests largely preserve out-of-distribution instruction-following performance.
- **Physical Intelligence:** π*0.6 trains autonomous robot experience and expert corrections back into the VLA, more than doubling throughput and roughly halving failures on some of its hardest tasks.

Linear attention finds a place alongside full attention

Linear attention summarizes earlier tokens in a fixed-size memory, reducing the cost of long contexts. Full attention keeps direct access to individual tokens that this summary can lose. Qwen combines the two, making linear attention a useful component of a hybrid model.

- Qwen3.8-Flash-Next beats its predecessor on 8 of 14 benchmarks using about a ninth of the training FLOPs. This gain includes other architecture and training changes.
- Other labs are trying this too. Kimi Linear generates tokens 2.3x faster than full attention at 1M context, one sequence at a time. Moonshot also uses its delta-attention technique in the 2.8T-parameter Kimi K3.

Three linear layers per attention layer



Sparse attention (QSA)

Reads selected tokens

Linear attention (GDN)

Keeps a compact memory

DiffusionGemma uses parallel drafting to speed up local text generation

When a GPU serves one user, moving model weights from memory can take longer than computing the next token. Google's DiffusionGemma drafts a whole block of text, then revises it in parallel. This gives the GPU more work at once and speeds up token output, with a trade-off in answer quality.

- DiffusionGemma revises a 256-token block over several passes, then moves to the next. Extra training reduces the passes needed. The four steps shown are illustrative.
- Google reports up to 4x faster token output on dedicated GPUs serving one or a few users. Standard Gemma 4 still produces higher-quality answers, though.



Gyms for AI: there's a bench for that

Software accounts for 57% of verified citations in this selection; Terminal-Bench alone contributes 45%. Totals sum Google Scholar counts for 46 of 58 benchmark releases introduced or refreshed since October 2025.

Write software — 483

Build software and complete terminal tasks

Terminal-Bench 2.0*	383
ProgramBench	48
NL2Repo-Bench	20

Use computers — 56

Carry out tasks across websites, apps and files

OSWorld 2.0	22
ClawBench	10
Workspace-Bench	7

Learn and remember — 65

Learn from context and remember future tasks

CL-bench	42
PM-Bench	6
Context-Bench	n/a

Improve AI — 82

Train models and improve how agents work

PostTrainBench	44
AIRS-Bench	23
HarnessOpt-Bench	5

Do science — 57

Solve research problems and discover hidden rules

Collider-Bench	10
Riemann-Bench	6
DiG-bench	2

Run a business — 8

Manage a business and interpret financial data

CEO-Bench	4
FinSheet-Bench	2
Vending-Bench 2*	n/a

Health and security — 59

Test clinical advice, security and lie detection

Liars' Bench	16
EVMbench	10
MedConsultBench	2

See, hear and act — 43

Interpret sound and video, reason about actions

RoboWM-Bench	23
Butter-Bench	2
VideoASMR-Bench	n/a

Note: totals sum verified Google Scholar counts across the curated set. Snapshot: October 7, 2026. n/a = no count verified.

** Reported use by at least two frontier labs.*

But who benchmarks the benchmarks?

Epoch AI finds substantive flaws in nine of its first 15 benchmark reviews. Broken scoring, exploitable environments, and uneven evaluation conditions can distort the results used to compare models.

- Epoch inspects tasks, scoring logic, prompts, tools, and resource limits. Insufficient access means "Not enough info."
- Reviewers sample 50 random tasks, or all if fewer, checking for hidden requirements, wrong scoring, and shortcuts.
- The default failure threshold is ⩾20% faulty sampled tasks or systemic grading issues. Unfair setups and inconsistent versions can also fail.

Flawed 9
At least one substantive defect.
Terminal-Bench 4.0.0, SWE-bench Verified.

Verified 4
Meets minimum standards, with caveats.
PostTrainBench v1.1, WeirdML v2.

Not enough info 2
Cannot support a quality verdict.
CritPt and FrontierCode.

Benchmarks built to last for years are now saturating in months

Every headline eval in the 2025 State of AI Report has hit or neared its ceiling. On Epoch AI's independent runs the best AIME score is 100%, GPQA Diamond 95.8% and FrontierMath Tiers 1 to 3 93.7%, and ARC-AGI-2 went from 18% to 95% in eleven months.

- GPQA Diamond: the #1 and #5 models are 1 point apart, and Epoch estimates 5 to 10% of questions are mislabeled, so the ceiling sits below 100.
- ARC-AGI-2: 18.3% (GPT-5 Pro, Oct 2025) to 95.0% (GPT-6 Astra, Sep 2026), as cost per task fell from $7.14 to $1.12. GPT-6.1 Sol now scores 94.2% for $0.25.
- In January 2026, Artificial Analysis dropped MMLU-Pro, AIME 2025 and LiveCodeBench because they no longer discriminate.



The hardest math benchmark went from 22% to 100% in fourteen months

FrontierMath Tier 4 was built as research-level math that should hold out for years. On Epoch's corrected v2 set, GPT-5 scored 22% in August 2025, GPT-5.4 Pro 59% in March and Claude Fable 5 90% in June. In September GPT-6 Astra hit 98% and GPT-6.1 Sol solved all 41 private problems.

- OpenAI funded FrontierMath and has access to 30 of the original 50 Tier 4 problems, but Claude Opus 5.5 also scores 95%.
- Epoch now tracks 49 unsolved research problems and credits AI with nine solutions, four without human help. GPT-6 Astra supplied the main proof of one rated a major advance.
- Surge's private Riemann-Bench still has headroom: GPT-5.6 Sol leads with 74.4%.



ARC-AGI-3 lasted five months...depending on the harness, Astra hits 63% or 99.9%

In March 2026, ARC-AGI-3 introduced hundreds of fully interactive, video game style turn-based environments, meant to be much harder than ARC-AGI-2's static visual puzzles. Although humans score 100%, initial scores by frontier models were a measly 0.5%. But then Claude Opus 5 reached 30.2% in July, GPT-6 Astra changed the game in September and GPT-6.1 Sol followed at 52.7%.

- Astra achieved 62.7% on the standard ARC Prize harness and 99.9% with a state-persistent adapter, which ran 3.66x faster on 49% fewer tokens.
- It outperforms the median human in action efficiency on 96% of levels.
- Astra is considered a "major breakthrough" by ARC developers for its novel symbolic modeling capabilities.





Hard benchmarks do not always separate leading models

Which evals still tell models apart? We plot each benchmark's best published score against its first-to-fifth model gap. ARC-AGI-3 and MirrorCode remain the widest separators, at 55 and 46 points.

- Terminal-Bench 4.0, APEX-Agents 1.1 and FrontierSWE v2 have first-to-fifth gaps of 16, 14 and 11 points.
- CritPt remains hard (top score 32%), yet its top three are within 0.6 points. APEX now tops out at 82%, with an 8.7-point top-three gap: its leaders are no longer as tightly clustered.
- Other leaders remain close: DeepSWE's top five score about 70–74%. FrontierCode 1.1 spans 2.6 points. These are point estimates across different tested model rosters, not significance tests.



Long-horizon coding rankings change with the task and the evaluation budget

FrontierSWE gives agents 20 hours to build software in a common harness. MirrorCode asks them to rebuild programs from documentation and a runnable reference, allowing up to seven days and 10B tokens. These different tests produce different leaders.

- FrontierSWE: Astra scores 65.5% versus Opus 5.5's 62.3%, at $1,030 versus $99 per trial.
- MirrorCode: Opus 5.5 passes every hidden test on 77% of tasks at max effort, versus Astra's 47% at high effort.
- The scores measure different outcomes under different budgets. Neither establishes a universal coding ranking.



High scores can hide unfinished scientific analyses and desk work

FrontierChallenge and EarthVerse test scientific analyses and natural-hazard investigations, while OSWorld 2.0 tests office workflows such as expense claims. Partial scores credit individual requirements met. A correct calculation or document can earn points even when the report is incomplete or the claim is never submitted.

- On 97 scientific workflows in FrontierChallenge, GPT-5.6 Sol scores 87.9/100 but fully completes only 20.6% of tasks.
- On EarthVerse's 405 natural-hazard investigations, the same model gets 82.1% of required answer items right. Only 34.8% of tasks reach the 95% threshold.
- On OSWorld 2.0's 108 computer tasks, Opus 5 earns 77.7% partial credit but completes 44.3%. Missed approvals or unsubmitted forms can leave otherwise useful work unfinished.



METR needs harder tasks to reliably measure the strongest models

METR's 50% time horizon is the length of task, measured in human expert hours, that an agent is predicted to complete half the time. It measures task difficulty, not time without human oversight. The strongest models now reach the sparsely tested end of the scale, so longer horizons are becoming harder to measure reliably.

- Estimates rose from 4.9h for Opus 4.5 to 12.0h for Opus 4.6 and 17.4h for early Mythos Preview. The latter's 95% confidence interval spans 8.5-55.1h.
- Only five tasks take humans more than 16h, so estimates up there are sensitive to scoring choices. METR warns that results above 16h are unreliable.
- METR's dashboard has no estimate for GPT-6 Astra, Fable 5.1 or Opus 5.5. June's GPT-5.6 Sol estimate swung with how cheating was scored, and METR called none of the results robust.

50% time horizon and 95% confidence intervals



The house wins: every model loses money on KellyBench sports betting

Frontier models must learn to solve long-horizon tasks in changing environments. To test this, General Reasoning built KellyBench, a simulated English Premier League market where agents build ML models to trade on matches and maximize gains over a season. Every model lost money on average, highlighting a remaining capability gap for frontier models on ultra-long-horizon tasks.

- Agents receive the 2023-24 season's lineups, results, public odds and match statistics in sequence, with £100k to build models, find an edge and size bets.
- All 12 models lose money on average over 5 seeds, and six go bankrupt in at least one. Opus 4.7 ends with £96k and GPT-5.5 with £90k, but most do far worse.
- GPT-5.5's strategies score highest on a 52-point expert rubric for sophistication, at just 30%.



The highest-earning e-commerce agent is among the worst at avoiding fraud

E-CommerceBench gives 18 models CNY 100k to run up to four online stores for 365 simulated days. Built by Alibaba and HKUST using Taobao and Tmall data, it tests purchasing, pricing and cash management. A high return can hide weak supplier screening and little learning from experience.

- GPT-5.6 Sol averages CNY 1.43M over five runs, but sends 18.48% of order spending to fraudulent suppliers. Opus 4.7 sends 0.12%.
- Prices and deals follow rules, unlike Vending-Bench's LLM-driven suppliers. Agents face 6.9k products, 576 suppliers and changing demand, with an LLM voicing replies.
- On repeat purchases, 16 of 18 models show no clear progress in bargaining prices down. A year of trading rarely translates into better buying.



Frontier models can play unfamiliar games, but struggle to discover the rules

DiG-bench gives agents 70 text-based games that have never appeared online. Text is used to isolate discovery as the operative challenge. At each turn, agents see the current game state and available actions, but not the rules or win condition, which they must infer through their own experimentation.

- Forty-nine of the 70 games are private to limit contamination and tuning. Every game was solved by at least one human on first exposure, so its rules are discoverable.
- Opus 5 solved 50/70, but frontier models together solved only 9/20 in the two hardest tiers. General-purpose agent harnesses did not help.
- Rule discovery, not execution, is the bottleneck: Gemini 3.1 Pro rose from 18/70 to 69/70 when given the true rules but no strategy.



Multimodality became continuous interaction

Thinking Machines previewed a continuous interaction model that handles interaction in one learned loop, rather than through external scaffolding. Previous 'live' experiences built on top of multimodal models would scaffold ASR, vision, dialogue and TTS into a pipeline. Interaction models may still invoke an external asynchronous background reasoner or make tool calls.

- Interaction models chunk time into ~200ms micro-turns, removing the traditional user/assistant turn boundary
- At each step the models see, listen and speak, enabling overlaps, silence, interruption and visual cues to become native behaviour
- The models also process text tokens at each step to call tools, interact with the environment or invoke a reasoner model.
- In China, where livestreaming is a major retail channel, labs are investing in interaction models. MiniCPM-o 4.5 is a 9B full-duplex interaction model, which can run on edge devices with <12GB RAM. ByteDance's SeedRealtime is another example.



Figure 4: An illustration of the interaction model architecture for a single 200ms micro-turn. The model takes in any subset of text, audio, or video and predicts text and audio.

Generative video goes real time and lets a streamer steer it!

Most video models return a finished clip after you've prompted it and waited a couple seconds. Media-focused inference company fal took MiniMax's open weights H3 video and audio model to create H3 Max, which adds data for prompt following and aesthetics, plus a serving engine and GPU kernels optimized alongside the model.

- fal reports generating a five-second clip in under three seconds, about 35x the throughput of the official H3 endpoint.
- Their Director mode carries 39 frames into each new segment and remembers prior prompts. It drops overlapping frames so successive segments play continuously, giving you the real-time streaming feel.
- On fal.live, viewers vote on what happens next. At 24 FPS, prompts steer the next segment, opening interactive TV with a delay before changes appear.



World models let agents learn and test actions in simulated environments

A world model predicts what happens after an action. Repeating those predictions creates an imagined rollout. Agents can use it to plan, generate training experience or test behavior. The following examples cover generated worlds, learned state representations, driving and robot control.



Note: The diagram shows three possible uses, not a one-to-one map to the following slides.

SIMA 2 improves in generated worlds, with Gemini setting and scoring the tasks

DeepMind paired Genie 3's generated worlds with SIMA 2. Gemini proposes tasks, scores video of each attempt and supplies feedback for retraining. Gains transfer to held-out worlds, but this initial result centers on navigation and uses Gemini's own scoring rubric.

Genie 3 generates a world → SIMA 2 acts in it → Gemini sets tasks and scores → SIMA 2 retrains on scores → Test: held-out worlds

- Trained on urban Genie 3 worlds, SIMA 2 improves on nearly all training tasks, often by 25 points or more on the 0 to 100 rubric (DeepMind, Dec 2025).
- The gains transfer: on most held-out natural-world tasks, the self-improved agent beats the initial one (figure).
- The authors call this initial, navigation-centered evidence, scored by the same Gemini model that drives the loop.



Agora-2 is a learned game engine for humans and AI agents

Odyssey trains on Diablo II video paired with actions and game state, learning how participants interact. Four humans and sixteen AI agents can share a simulation shaped by their collective actions.

- A simulation transformer predicts how participants affect one another. A shared state tracks their positions and interactions, including when they leave a player's view.
- A flow-matching video transformer generates each perspective. Training removes visual history so it must use the supplied state, and gives extra weight to errors on the characters driving the action.
- Alongside efforts to replace game engines with learned models, coding agents are helping developers modify and combine existing games, using established modding tools and reverse-engineered code.



World models can plan without learning to paint every pixel

A robot planning a route needs to predict where its actions lead. Meta's V-JEPA 2.1 learns visual features by predicting representations of video, rather than reconstructing pixels. Using those features in a navigation world model cuts planning time roughly 10x while preserving trajectory accuracy.

- Given a current view and a goal image, the planner searches for a two-second route using the Navigation World Models (NWM) setup.
- The baseline also plans in latent space, but learns it by reconstructing images. Meta changes the representation, prediction target and sampling method.
- Plans need 8 refinement steps instead of 128, with average trajectory error nearly unchanged across four datasets (3.03 vs. 2.98).



Note: Open-loop benchmark. Colors show learned features in three example plans.

Wayve's GAIA world model becomes a bonafide driving simulator

2023 - GAIA-1

Predict a driving video

- Text and actions guide next-token prediction and video decoding.
- One camera view, trained on 4,700 hours of London driving.

Text changes snow and lighting

Mar 2025 - GAIA-2

Generate the whole view

- Five synchronized cameras with latent diffusion.
- 8.4B parameters. Control traffic and weather in the UK, US and Germany.

Five cameras, three vehicle rigs

Dec 2025 - GAIA-3

Vary a recorded scene

- Change the car's path, preserve recorded traffic.
- 15B parameters and about 10x GAIA-2's training data.

Prescribed path, recorded traffic

Aug 2026 - GAIA-4

Put the driver in control

- Camera and radar generation follows the AI Driver's decisions.
- Compare models or rerun interventions on recorded scenarios.



Real and generated radar

Odyssey-3 demonstrates a world model can adapt to physical and virtual tasks

Odyssey-3 is an autoregressive diffusion transformer pretrained on visual observations to simulate how the world evolves over time. Observation-action pairs then train a decoder to turn its representations into controls, which the company evaluates on real-world driving tasks, dual arm manipulation, humanoids and gameplay.

- With the backbone frozen, 20 hours of simulated driving data produced a road-driving policy. Simulation-trained policies reached 77% of real-data policies' distance between safety-driver interventions.
- Tens of hours of robot data supported manipulation and Flexion's humanoid control. Robot arms recovered from missed grasps without demonstrations of those recoveries.
- A policy trained on ~2 hours of GTA footage produced horseback movement in Red Dead Redemption 2 without retraining, an early example of transfer.

Driving on Indian roads

Robot-arm manipulation

Flexion humanoid

GTA to RDR2 transfer

Robotics gets its GPT-2 moment: generalization now scales with pre-training

- **Skild's S1 shows in-context learning emerging with scale. On unseen tasks, one video prompt and zero fine-tuning sees the model climb from ~0% success at 1k pre-training hours to 66% at 100k hours, while a language-prompted VLA trained on identical data and compute stays at 9%. Sunday Robotics sees the same shape on laundry folding: the in-domain vs unseen-home gap falls from 82% to ~0% with pretraining scale.**



SKILD AI



SUNDAY

Teaching robots requires data about how to act

Robots learn to manipulate objects from demonstrations that connect what they see with how to move. People can provide these by controlling a robot, using handheld grippers, or wearing cameras as they work. Each approach differs in how the recorded movements are translated into robot actions.

Teleoperation

Direct robot demonstrations

A person controls a robot while its observations and actions are recorded.

Handheld grippers (UMI)

Demonstrations without a robot

Tracking captures the path and opening of a person's handheld grippers.

Egocentric human video

Human demonstrations at scale

Models estimate hand and wrist movements from video, then transfer them to a robot.

For π0.7, context makes imperfect robot data useful

Naive training on diverse robot data would average across strategies and degrade the learned policy. To fix this, each training episode is richly annotated with context such as what the robot should do and how the action was done, so demonstrations, failures, and web data all become usable signal.

- π0.7's prompt combines subtask language, generated subgoal images, and metadata for speed, quality, mistakes, and control mode.
- Those labels let one model train on failures, autonomous rollouts, and expert demonstrations, then request the desired behavior at inference time.
- On laundry, throughput improved as lower-quality data was added with metadata, but fell without it. Removing the most task-diverse 20% also cut success on three unseen tasks.



A robot turns five minutes of play into reusable skills

A kitchen task combines familiar actions in a new order: open a container, put something inside, then close it. Imitation learning often learns the whole sequence, while classical planners need hand-written rules. Penn's SymSkill learns both reusable motions and the conditions for using them from unsegmented demonstrations.

- A vision-language model identifies objects offline. Relative object positions define learned conditions, such as where the gripper must be before an action.
- It reaches 85% success across 12 single-step RoboCasa tasks. Separately, a real Franka learns from five minutes of play and performs tasks up to 12 steps.
- A planner reorders skills and recovers after disturbances. Recombining practiced movements avoids collecting demonstrations of every possible sequence.



Robot planners use execution history to choose the next action

Complex robot tasks split into deciding what to do next and executing the movement. This is often called a System 2 / System 1 architecture: a reasoning planner directs a fast motor policy. Google's Gemini ER 2 monitors execution and adjusts its instructions, while NVIDIA's Vesta uses memory to plan across multiple steps.

- ER 2 tracks live video and retries failures. In Google's internal tests with a real VLA, replacing ER 1.6 with ER 2 raises success from 48.6% to 60.0%.
- Vesta pairs an 8B Qwen3-VL planner with GR00T N1.6. On counting, drawer-search, and hidden-object tasks, it adds 38.3 points of success over the actor alone.
- Joint training also beats Vesta's specialist ablations in navigation and embodied reasoning. Real-robot evidence remains limited to 20 trials per task on one YAM setup.



Vesta remembers the candy inside the box

Close the box

Choose the matching tray

With a longer memory, a robot can improve long-horizon task completion

Long assemblies can look similar at different stages, so the latest camera frame may not reveal what to do next. Most robot policies see only a short history. RoboTTT adds an adaptive memory to GR00T N1.7, helping it track progress and recover without retaining every frame.

- Across three YAM assembly tasks, RoboTTT scores 79% task progress versus 42% without memory and 56% with recurrent Gated DeltaNet memory.
- Fast weights compress observations as they arrive. Performance improves with up to 8k timesteps of training context, while inference cost stays constant.
- On the five-minute Gear Bot assembly, it finishes 2/10 trials versus zero for every baseline. Better task tracking is promising, but reliable completion is still difficult.

Gear Bot: a five-minute, ten-stage assembly



Simulation is a bedrock of robotic reality

Robot policies are costly to test on hardware, while hand-built simulators may rank them incorrectly. SimFoundry reconstructs interactive scenes from video and generates related objects, layouts, and tasks. It tests whether scores in those scenes predict performance on real robots.

- Seven tasks test policies including π0, π0.5, GR00T N1.6/N1.7, and DreamZero. Simulated and real scores have a mean correlation of 0.911.
- Depth, segmentation, and 3D models recover objects and movable parts. Physics checks stabilize the scene, then new layouts expand the training data.
- This could reduce hardware needed for model selection. Evidence covers selected tabletop tasks, with optional manual refinement, not arbitrary environments.

Real scenes become interactive variations

A humanoid learns stair climbing in four hours of simulation

PPO trains robots but discards past experience. Soft Actor-Critic reuses it but can be unstable on complex bodies. FlashSAC uses larger networks and batches with fewer updates. Batch normalization and a classification loss stabilize action-value learning and limit error amplification.

- 4,096 simulated Unitree G1s learn stair climbing in 4h on one A100, versus nearly 20h with PPO. The controller runs on real stairs without further fine-tuning.
- Across 60+ tasks in ten simulators, FlashSAC improves performance and training speed over PPO and FastTD3, especially on high-dimensional control.
- Transfer uses randomized physics and an established sim-to-real setup. The draw is a reusable, faster learning recipe, building on earlier transfer successes.

Simulation training to stair climbing



Robots must get a grip by learning contact physics

Human and robot hands differ, so copying joint positions can produce a grasp that slips or cannot lift a lid. OmniRetarget and VideoMimic preserve contact geometry. CHORD goes further, rewarding contacts that can exert similar forces and torques on the object.

- CHORD trains RL policies from human hand-object demonstrations. It matches the forces contacts could support, rather than measuring the person's actual force.
- Across 1,831 simulated tasks, it reports 82.1% success. Ablations beat contact-position-only rewards: nearby contacts need not be mechanically equivalent.
- Real Dexmate tests use Sharpa hands and motion capture. The controller follows a fixed demonstration without replanning, so the scale claim comes from simulation.

CHORD: opening a lid requires useful contact



Astra drives a robot arm without a robot policy, but can't handle contact or refuse danger

Robots normally need a VLA trained on robot data to turn camera images into motion. The RoboDojo team instead gave OpenAI's GPT-6 Astra three cameras and one tool that moves the gripper to a point. Robocurve then tested whether models refuse harmful requests once they control real arms. It works, but is slow...

- Across 42 simulated tasks, Astra scores 28.97 versus 24.90 for DM0.5, the best of 40 trained policies. GPT-5.5 scores 1.13 with the same tool.
- Astra wins on geometry and language: 60% on Push T versus 0.7% for the best VLA. It scores 0% on tube insertion, where DM0.5 reaches 59%.
- RoboDojo halted hardware tests after Astra damaged equipment. In a Robocurve X thread without published methods, Astra attempted 97% of harmful requests and Fable 5.1 80%. MolmoAct2 never refused, but completed only 6%.

Simulated task success: Astra vs the best trained VLA

Asked to stab a human-like figure (a prop doll)

GPT-6 Astra

MolmoAct2 (VLA)

Coding agents run experiments on a robot fleet

ENPIRE gives coding agents a repeatable robot experiment: reset the scene, run a policy, check the outcome, and inspect failures. People first help validate those tools and then the agents can change training code and control strategies, rather than rely on a researcher to tune each attempt.

- Codex (GPT-5.5), Claude Code (Opus 4.7), and Kimi Code test policies on YAM arms. Tasks include pin insertion, GPU insertion, and cutting zip ties.
- On pin insertion, eight agent-robot pairs reach near-perfect performance in ~40 minutes versus over 90 for one. Success allows up to eight recovery attempts.
- Agents can combine RL, imitation, and procedural control. More robots speed experiments, but token costs grow disproportionately and human setup remains necessary.

Eight YAM stations test policies in parallel

GPU insertion

Pin insertion

Real-world lab data can make an open model into a capable materials analyst

X-ray diffraction (XRD) reveals which crystalline materials an experiment produced, but overlapping signals can take scientists hours to interpret. Periodic Labs started with Kimi K2.6 and extended it with scientific midtraining (a multimodal blend of academic literature, code, and experimental data to build broad scientific understanding), then reinforcement learning on its experimental data for XRD.

- On 134 difficult lab samples, Neon succeeds 55.3% of the time, up from its base model's 2.7% and ahead of Astra and Fable 5.1 in the same Periodic harness.
- Midtraining on literature, code and experiments improves subsequent RL. Expert-calibrated LLM judges supply training feedback.
- To connect lab hardware to frontier agents, Anthropic released a preview of Model Hardware Standard, the MCP for labs.



OpenAI graduates from Erdős problems to a $1M Millennium Prize problem

Whether smooth three-dimensional fluid flow can develop a singularity had remained unresolved for roughly 90 years. OpenAI's system constructed such a breakdown under external forcing. The unforced Navier-Stokes case remains open.

- In August, Astra resolved three Erdős problems about when patterns must appear in networks, with proofs checked by the Lean proof assistant.
- 10,000 agents ran for 88 hours, but Noam Brown credits multi-agent work with under 10% of the Navier-Stokes result.
- Clay: apparently settled, assessment ongoing. OpenAI will not claim the prize.
- On October 6, OpenAI released 722 manuscripts in 372 result families from an unreleased model, with partial Lean verification.



Claude improves a longstanding bound related to the Riemann hypothesis

Prime numbers have a predictable average density, but their spacing is irregular. The Riemann hypothesis would tightly bound the error in estimates of how many primes lie below a given number. Claude combined existing mathematics to raise a related proven lower bound from 41.67% to 67.25%.

- The hypothesis puts all relevant zeros of the zeta function, which encodes primes, on one line. A proof must cover infinitely many zeros, beyond any numerical check.
- Claude proved at least 67.25% of the nontrivial zeros are on that line and simple, meaning not repeated, without assuming the hypothesis.
- The model connected existing research to prove a new theorem. The full hypothesis remains unresolved, and the remaining zeros are not shown to be off the line.



Frontier models more than doubled the best Terminal-Bench Science score in weeks

Terminal-Bench Science 0.1 tests agents on 70 research-derived workflows in runnable software environments. At release in August the best model, Opus 5, solved 30%. On the current leaderboard, GPT-6 Astra now solves 68.1% and Opus 5.5 63.3%.

- Tasks span data analysis, simulation and imaging, not full research projects.
- At maximum effort Astra and Opus 5.5 cost $23 to $24 per task. Fable 5.1 scores 40.0% (52.6% in Anthropic's run).
- Off the leaderboard, OpenAI reports GPT-6.1 Sol at 57.0% for $5.47 per task, Anthropic Sonnet 5.5 at 59.9%.



Verification cuts fabricated results, while human scientific oversight remains essential

Thirty experts reviewed 150 manuscripts on 50 matched topics. Removing Co-Scientist's reliability modules raised invalidating result hallucinations from 4% to 46%. A separate physical experiment in the same study still relied on humans to set constraints and validate the result.

- The full system reduced invalidating result hallucinations to 4%, versus 46% in the matched ablation and 90% for Agent Laboratory.
- Severe methodology failures remained in 24% of papers and severe plagiarism in 16%.
- Gemini generated a machine-executable recipe to grow 2D electronic materials. Humans loaded the samples and validated successful growth on the first attempt.



Nearly half of frontier models' "done" claims in lab-handling tasks were incomplete

Mecka gave three frontier models camera views and control of robot arms, with no demonstrations or fine-tuning. Human reviewers graded nine labware tasks across 540 attempts. Completion remained low, and a model saying "done" was often not evidence that it had finished.

- 89 of 192 "done" declarations were incomplete: 79 partial completions and 10 failures.
- Only Opus completed any hard task: two successes in 60 attempts.
- These are labware-handling tasks, not tests of autonomous scientific discovery.



Protein language models scale from sequence to structure and function

ESM Cambrian (ESMC) learns protein sequences by predicting hidden amino acids. ESMFold2 uses what ESMC learns to predict the 3D structure of proteins and how they fit together. Biohub used these models to design binders - proteins that attach to a chosen disease target - and tested selected designs in the lab.

- From sequences alone, ESMC learns which amino acids lie close together in a folded protein, even when far apart along its chain.
- Testing 84 designs per condition, more search and ranking improved hit rates in 9 of 10 tests. Designs were minibinders or antibody binding parts joined in one chain (scFvs).
- A PD-L1 binder - which helps the immune system attack cancer - designed with ESMC needed 1.6 nM for half-maximal signaling recovery, versus 2.6 nM for the control. Less protein is needed for this effect.



IsoDDE and Pearl jointly predict proteins and bound drug molecules

Cofolding models take a protein sequence and a drug's chemical structure and predict their joint 3D arrangement, allowing the protein to change shape around the drug. Isomorphic Labs' IsoDDE also predicts binding strength and potential binding sites. Genesis's Pearl lets researchers guide predictions with known structures.

- IsoDDE ranks candidate complexes by confidence and is trained on PDB structures through Sept 2021. Across 60 low-similarity complexes, top-ranked accuracy was 50.0% versus AlphaFold 3's 23.3%. The report doesn't detail the architecture and training recipe.
- Pearl's trunk learns pairwise relationships of the protein and ligand. A rotation-equivariant diffusion denoises atomic coordinates: rotating the input rotates the prediction.
- Pearl's five-stage training mixes experimental, predicted and physics-generated complexes. Protein, cofactor and ligand templates guide binding-pocket predictions.

Predicting an unfamiliar protein-drug interaction



Faster affinity prediction lets drug designers screen more candidates

TerraBind and Nesso-1 skip full atom-by-atom generation to predict binding strength faster. TerraBind also reports better agreement with measured affinity: Pearson correlation is 16% higher on CASP16 and 20% higher across 18 proprietary assay targets than Boltz-2. Generalization remains a challenge.

TerraBind: 26.6x faster in its test



Feb 2026. A6000, 196 tokens, 10 pose samples/complex. End-to-end timing includes pose generation.

Nesso-1: 1.0-2.7 seconds per prediction



Aug 2026 preprint. H100, 10 compounds/target. Nesso-1 (blue), Boltz-2 (gray). Excludes fixed loading/MSA costs.

Latent-X2 jointly generates binder sequences and atomic structures

Latent-X2 is an all-atom generative model that designs protein binders together with their interactions with a target. It jointly generates amino-acid identities and 3D coordinates. Latent-Y is the agent that turns research goals into model inputs and selects candidates for lab testing.

- X2 takes as input a target sequence and backbone, binding-site residues and binder format. Antibodies add a scaffold and binding-loop lengths. The target and binder share a 512-residue context.
- X1 is trained on the PDB and AlphaFold structures, while X2 shares its training cutoff. X2's full data mix, architecture and training objective remain undisclosed.
- Structure predictors filter for confidence and agreement with the generated complex. Testing 4-24 designs per antibody format per target yielded binders for 9/18 targets.

Latent-Y applies X2 to a prolactin-binding task

Prompt: disrupt prolactin receptor binding



Using a binding predictor more than doubles the yield of designed nanobodies

BoltzProt-1 generates protein binders and uses BoltzPPI, a protein-interaction predictor, to select designs for laboratory testing. Compared with ranking by structure confidence alone, it raised the confirmed hit rate from 3.3% to 8.0% across ten novel targets.

- Across ten novel targets, interaction-based ranking raised confirmed binders from 5 to 12 among 150 tested designs per method (i.e. 3.3% to 8.0%).
- Seven of the 12 confirmed binders passed every developability test, including stability and unwanted binding.
- The companion BoltzMol-1 pipeline found small-molecule hits on 6 of 10 targets, testing 28-51 compounds each.
- Protein candidates still need downstream optimization.



Chai's designed antibodies pass laboratory tests beyond binding

Antibodies must bind their targets and remain stable enough to manufacture and use. Chai-1 predicts molecular structures, while Chai-2 generates new binders, including full antibodies. Chai's detailed experimental study tests their drug-like properties, while its newer Chai-3 has entered pharma partnerships.

- Among 88 designed antibodies against 28 targets, 86% had at most one developability flag. For 24 targets, at least one design had no flags.
- Chai-2 found binders for all six tested GPCRs, membrane receptors that are difficult antibody targets. Designs activated two of the receptors.
- Chai says Chai-3 doubles its predecessor's success rate. The public announcement does not establish a matched denominator, so the chart uses Chai-2 data.



Designed antibodies direct T cells toward a cancer mutation in lab assays

Cells display fragments of internal proteins on surface molecules called MHC. Nabla Bio's JAM-2 generates antibodies that recognize these fragments, including a cancer-associated KRAS mutation. Joining a designed antibody to a T-cell-binding component lets it recruit immune cells to kill cells displaying the fragment.

- Screening about 84,000 designs per target recovered binders against all five targets.
- A selected KRAS G12V design reached half-maximal cell killing at 0.07 nM versus 0.48 nM for the benchmark antibody. Lower concentration means greater potency.
- The leads spared wild-type controls in these assays. Target cells were artificially loaded with peptides, so natural tumor recognition remains unproven here.

Recognition of a single mutant amino acid



Orange: antibody. Green: MHC. Magenta: KRAS fragment. The mutant Val12 side chain fits the antibody pocket. Selected structural validation.

An alignment technique from chatbots produced heat-stable flu antigens

Protein language models reward sequences that look natural, which is not the same as sequences that work. ProteinDPO borrows direct preference optimization, the method used to align chatbots to human feedback, and trains it on physical stability measurements instead.

- Preferences came from ~660,000 stability measurements on 405 small protein domains.
- With no hemagglutinin training data, 36 of 45 H5 designs kept antibody binding and held or improved stability.
- One nine-mutation design gained 17°C of melting temperature, and +13°C and +32°C when moved to 2024 strains.



AI can design working bacteriophage genomes, but cannot fully predict their biology

ΦX174 is a virus that infects and kills *E. coli*. Its small genome has overlapping genes, so one DNA change can affect several proteins, which makes designing its genome a challenging AI task. Stanford and Arc used their Evo 1 and Evo 2 models, DNA language models trained on natural genomes to predict and generate DNA sequences, to create functional phage genomes.

- 16 of 285 assembled designs produced viable phages. A cocktail of these phages evolved to overcome resistance in laboratory-cultured *E. coli*.
- An independent reanalysis found Evo 2 scores ranked viable genomes well (AUC 0.86), but their designs didn't deviate far from their natural relatives.
- Further validation found that about half of single-nucleotide changes made by the models impaired the phage's fitness. The ability of AI models to predict this phenotype wasn't strong.

Whole-genome design



Predicting viability (AUC)



Section 2: Industry

OpenAI and Anthropic's revenue are >3x'ing YoY, each time from a higher base

The two labs are now generating a combined $105B revenue a year, up from $30B at the start of 2026. Their run rates grew 3.6x in 2024, 4.7x in 2025, and are already 3.5x in the first eight months of 2026.

- OpenAI's run rate topped $40B in August 2026, roughly doubling from $21.4B at the end of 2025.
- Anthropic reached a $65B run rate in July, up from $9B entering the year, per its letter to investors.
- OpenAI says gross cloud accounting inflates Anthropic's revenue by up to $8B. The FT reports its >80% gross margin excludes partner revenue sharing and model training.



How does $105B of AI revenue compare with the industries AI is disrupting?

OpenAI and Anthropic's $105B revenue run rate rivals the service businesses they aim to disrupt. Broader annualized AI revenue estimates reach $229B at analyst firm Exponential View and ~$150B at The Economist, with different scopes and dates.

IT services: 2.1x TCS + Infosys



Accounting/tax: Almost half the Big 4



Legal: 1.6x UK legal services



Note: Labs: July/August 2026 run rate. TCS + Infosys: FY2026. Big Four: FY2025. UK legal: 2024. Scale comparison, not displaced revenue.

Codex users up 15x in seven months and Anthropic's $1M+ customers doubled in three

OpenAI's Codex went from 1.6M weekly users in early February to 25M active users on 31 August as their product marketing focused the app on knowledge work. Over 1,000 customers spend >$1M on Anthropic.

Codex users, millions



Claude Code run-rate

Customers over $1M a year



Note: from public data by OpenAI, Anthropic and their staff. Codex counts are weekly active users through June and 'active users' from July.

OpenAI and Anthropic capture 96% of token spending tracked by Ramp

Among businesses connecting their API usage to Ramp, Anthropic regained the spending lead in late September. Through October 3, it accounted for 52.4% of token spending, compared with OpenAI's 43.3%. Other providers together accounted for 4.2%.

Model market share changes with the platform and what is measured

OpenAI and Anthropic account for 20.7% of requests on OpenRouter. On October 4, open-weight models handled 62.7% of Vercel tokens but received 26.9% of spending. Different customer samples, workloads and prices mean these snapshots cannot be read as a single market-wide ranking.

openrouter **Share of text requests**

Week beginning September 28, 2026



Vercel **Open-weight share**

October 4, 2026 (daily snapshot)



Note: Different samples, metrics and periods. Platform activity is not global market share.

Top of the models: longevity is hard

Anthropic had at least one model in the top five for 51 of 52 weeks on Arena and 44 on Artificial Analysis. Only Anthropic and Google DeepMind cleared one-third of the year on each leaderboard. OpenAI cleared that threshold only on Artificial Analysis, and xAI only on Arena.





"We cannot miss this moment because we are distracted by side quests" - OpenAI

With raging success comes the need to prioritize. Ten OpenAI product surfaces have been retired or given a published shutdown date in 2026 alone. Anthropic never opened the fronts in the first place.



stateof.ai 2026

Focus is expensive: the abandoned categories have been claimed by competitors

As OpenAI narrows its focus, rivals pursue categories it left behind or never entered. Neolabs may resemble biotechs: proving a research bet could make them challengers or acquisition targets.

CATEGORY	STATUS AT THE TWO LABS	WHO IS BUILDING THERE NOW
Generative video	OpenAI exited: app Apr 2026, API Sep 2026. Anthropic never entered	**Runway** **Black Forest Labs** **Luma** **Kling** **Google Veo**
Image as a standalone product	DALL-E brand retired; image lives inside ChatGPT	**Midjourney** **Black Forest Labs** **Ideogram** **Recraft**
The AI browser	Atlas dead Aug 2026, folded into a Chrome extension and ChatGPT desktop	**Perplexity (Comet)** **Opera Neon** **The Browser Company**
Robotics	OpenAI disbanded 2021, restarted 2024-25; Anthropic never entered	**Physical Intelligence** **Skild** **Figure** **1X** **Covariant** **Generalist** **Sereact**
AI for science	Peripheral to both	**Periodic Labs** **Lila Sciences** **Edison Scientific** **Isomorphic** **Profluent**
Self-improving research systems	Internal only at both	**Mirendil** **Core Automation** **Discovery Loop**
Music	MuseNet and Jukebox abandoned; neither lab ships music	**Suno** **Udio** **ElevenLabs**

Founded by OpenAI or Anthropic alumni

DeepMind is the talent supply chain for its competition

While OpenAI attracts lots of public flack for the departure of its team members, far more staffers have left DeepMind for competitors. The heatmap shows people who worked at the row lab and later joined the column lab, directly or after a stint elsewhere.





A research bet can still pay off: Jev takes 27% of OpenRouter's classification requests

Choosing which tool to call or whether to flag a transaction is a classification task, not a writing task. TypeSafe spent two years building Jev around that distinction: a model that assigns probabilities to predefined answers without generating text and unlike prior generation ML, obviates the need for feature engineering. Its early adoption suggests a focused research bet can find demand even in a market crowded with frontier models.

- TypeSafe reports 70-500ms responses from a single parallel pass, at $0.042 per million input tokens and free output during early access.
- Vercel says ~13% of paid AI Gateway teams used Jev within 24 hours, twice GPT-5.6's share over the same window.
- On OpenRouter, Jev took 27% of weekly classification requests within ten days: uptake in one category, not overall usage or revenue.
- The company is reportedly on a $100M annualized run rate after 7 days.



Leading AI companies keep scaling beyond their first $100M

After reaching $100M, Legora and Sierra doubled in about six months and Harvey grew to $400M. Lovable now reports $600M and Cursor has been reported above $4B. Starting points differ across companies.

Months from stated starting point to $100M



Revenue in months since reaching $100M

Note: Launch: Higgsfield, Lovable, Kling, Sierra. $1M ARR: Cursor, Legora.
First revenue: ElevenLabs. Founding: Harvey (upper bound). Clocks and metrics differ.
Months are approximate. Cursor line ends at $1B; later >$4B at 17 months.

AI-native private companies grow about 3x as fast at the upper quartile

Standard Metrics compares companies where AI is the product ("AI native") with existing software businesses that have added it ("AI enabled"). In preliminary Q2 2026 data, revenue growth at the 75th percentile was 256% versus 90% at $1-20M in annualized revenue, and 172% versus 53% above $20M.



AI-native growth is fastest among newer companies and those selling to SMB/mid-market

AI natives outgrow AI-enabled SaaS in every founding cohort and customer segment. At the 75th percentile, YoY growth is 487% versus 199% for companies founded since 2020, and 303% versus 82% for SMB and mid-market sellers. Among enterprise-focused companies in Q1 2025's top growth quartile, 42% of AI natives stayed there a year later, versus 23% of AI-enabled SaaS and 28% of non-AI companies.



Standard Metrics

Note: Left panel data pools Q3 2025 to Q2 2026 for companies with $1M+ annualized revenue.

The top 1% of firms spend about 580x the median per employee on AI

In August 2026, the median firm in Ramp's top 1% spent $7,205 per employee per month, versus $12.50 for the median firm. A separate Ramp analysis finds that 1% of customers account for about 80% of observed spending on OpenAI and Anthropic.

Note: Monthly spend per employee. Panels use different scales. August 2026.

>50% of Claude user chats involve important work, usually under human direction

What are regular people using Claude for? And what does it tell us that AI spend and benchmarks don't? Researchers at Stanford's SALT Lab analyzed 249,834 consumer Claude.ai conversations from two weeks in spring 2026 through Anthropic's privacy-preserving Insights pipeline. The sample covers chat only, excluding Claude Code and Claude Cowork.

- 56% of conversations assigned a criticality tier were consequential or high-stakes work, and 12% were high stakes.
- Humans led the work with AI assisting in 72% of assessable conversations overall.
- Verbatim use of AI output declines from 21% on ephemeral tasks to 13% on high-stakes tasks.
- Friction appeared in 50% of all conversations, and users attempted active recovery in 79% of the conversations containing friction.



Codex adoption remains far higher inside OpenAI than among external users

How far along is agent adoption outside the labs? Codex data compare OpenAI staff with organizational and individual ChatGPT users. For context, a separate analysis of S&P 500 companies' AI disclosures found that 69% reported live deployments, but only 2% disclosed metrics tracked over time.

- 97.9% of active OpenAI workers used Codex in the preceding 28 days, compared with 17.3% of organizational users and 0.7% of individual users.
- The share of individual Codex users assigning at least one estimated eight-hour task rose from 2.1% in December 2025 to 25.6% in May 2026.

Codex usage relative to ChatGPT



Users by peak task complexity



Non-developers are growing usage of Codex faster than developers are

Weekly non-developer users grew faster than developers across individual, organizational, and OpenAI groups. From August 2025 to June 2026, individual non-developer users increased 137-fold, organizational users 189-fold, and OpenAI users 12-fold, the latter reflecting their already high baseline. This growth is also likely influenced by improved education and awareness of agentic capabilities.

Developers

Non-Developers

Non-developers' Codex use is growing faster than developers' use

Who is picking up coding agents now? Codex was built for software work, and engineering still dominates absolute usage. The fastest growth is now coming from legal, sales, recruiting and marketing, almost entirely from near-zero starting points.

- Since February 2026, weekly active enterprise Codex users grew 108x in legal, 41x in sales, 41x in recruiting and 26x in marketing, against 5x in engineering.
- Depth still favors software: in June 2026, Codex generated 26.8% of the average organizational engineer's combined ChatGPT and Codex output tokens, against 1.9% for the average legal user.
- Anthropic separately reports management, sales and legal as the fastest-growing non-software occupation groups using Claude Code.



VC-backed companies went from near parity to 10x on AI spend

In September 2023, the median VC-backed company spent $3.40 per employee per month, against $2.13 for other firms. By August 2026, VC-backed spend rose 24x over nearly three years, compared with 3.9x for other firms.



AI performance still varies widely across financial work

Claude Opus 5 scored 100% across 20 attempts on four structured accounting tasks. However, it passed only 12.3% of ATLAS-Finance's 100 simulated banking assignments, which require a correct workbook and proper delivery. Better environments, evaluations and expert training data may close this gap.

Mercor: structured accounting tasks

12 licensed CPAs worked alone, with a three-hour limit and no colleagues, clients or accumulated company context.



Each dot is an attempt: 23 human and 20 AI attempts.

ATLAS-Finance: whole-task pass rate

In one failed assignment, Opus 5 passed all 13 self-checks by validating against its own wrong financial assumption.

Top three models. No scored human baseline or error bars.

Heavy token users grew revenue 3x faster than light users over a 12 month period

BCG grouped 107 public technology companies above $500M in trailing-12-month revenue into quintiles by Cursor monthly token consumption, over April 2025 to March 2026. Median YoY revenue growth rises across every quintile, with the sharpest step from Q3 to Q4 rather than at the very top.



Heavy AI spenders hire faster...except for scientists

Ramp linked its card and bill-pay AI spend to Revelio headcount records for 21,559 US firms to compare them based on their AI usage. Heavy spenders, the top third at $33.67 per worker per month, added 10.2% headcount over two years and 12% at entry level, whereas light adopters never separated from the control group. Scientists are the exception, where both groups grow and converge by month 24. Almost all gains sit in tech companies...



stateof.ai 2026

Early AI labor studies point to risks for junior workers

Anthropic studied how AI affects jobs and learning. US labor data show tentative signs of weaker hiring among young workers in AI-exposed occupations. In a separate experiment, developers who used AI were less able to explain how the code worked and identify bugs afterward.

- No clear rise in unemployment in AI-exposed jobs relative to unexposed jobs since late 2022.
- Job starts appear to have slowed for 22-25-year-olds entering AI-exposed jobs. The cause remains uncertain.
- 52 developers learned Trio, a Python library for concurrent tasks, then took a 14-question quiz without AI. It tested code comprehension: scores were 50% after learning with AI versus 67% without it.



The quiz tested code reading, debugging and understanding of the library after two coding tasks. The speed gain from AI was not statistically significant. This measures immediate learning, not long-term skill loss.

AI in education: the best tutor is not a helpful assistant

A good tutor helps students solve problems themselves. That requires teaching behavior, not just correct answers. A classroom trial in Sierra Leone measured learning gains from teacher-led Gemini activities, while tutor benchmarks show why general assistants can still over-help.

- In 48 classrooms across 12 schools, 1,763 students were randomized to teacher-led Gemini activities or standard instruction. Math scores improved by 0.258 standard deviations after eight weeks.
- The 95% confidence interval was 0.027-0.488. This tests a structured classroom program, not unrestricted chatbot use or long-term learning.
- TutorMoments and MathTutorBench find that giving correct answers is different from teaching. Curriculum context and prompts that make students think remain product-design challenges.

The AI build-out is adding jobs even as some office roles shrink

The Economist estimates the creation of 320,000 extra US infrastructure jobs and 730,000 extra jobs in AI-related professions relative to broader hiring trends. Among office roles, employment grew for data scientists and paralegals but fell for data-entry clerks and customer-service staff.

Infrastructure



AI professions



Office jobs are diverging



Claude Cowork nuked $285B of public software value in Feb that was won back by Sept

In January, Anthropic shipped Claude Cowork, an app that wrapped Claude Code to make it more usable by knowledge workers with their own files and business workflows. As the company added plugins for legal, marketing and finance, markets freaked out and investors called the end of seat-based pricing and repriced the terminal value of SaaS revenue.

- The "SaaSpocalypse" wiped out nearly $285B of software market capitalization in early February. The S&P 500 software and services index fell 26% from its October 2025 peak.
- Hedge funds shorted $24B of software names in the year to date. The panic spread to cybersecurity after Claude Code Security launched on February 20.
- XSW rose 55% from its April low to August's peak, before pulling back to +44% by 11 September.

XSW daily closing share price ($)



OpenAI and Anthropic set up their own consultancies, funded by private equity

To accelerate enterprise adoption of their systems, the two labs launched services companies in May 2026 to provide deployment services, capitalized by the private equity firms whose portfolio companies are the customers. Their challenge, however, is being bounded to the stack of their parent company.

- Anthropic's venture with Blackstone, Hellman & Friedman and Goldman Sachs carries about $1.5B of committed capital.
- OpenAI's Deployment Company raised more than $4B at a $10B pre-money valuation from 19 investors led by TPG. Reports suggest that investors get a guaranteed 17.5% minimum annual return with capped upside, closer to credit than equity.
- Both built their deployment companies from the acquisition of smaller AI consultancies: Fractional AI for Anthropic and Tomoro for OpenAI.

	ODE with ANTHROPIC	OpenAI Deploy Co.
Capital	~$1.5B committed	>$4B raised
Valuation	Not disclosed	$10B pre-money
Founding partners	Blackstone, Hellman & Friedman, Goldman Sachs	TPG, Advent, Bain Capital, Brookfield
Structure	Joint venture	OpenAI-controlled joint venture, 17.5% guaranteed return

So, is intelligence too cheap to meter?

EpochAI find that the price for a given level of performance has fallen about 47% per quarter, or 13x per year. This makes AI the fastest cost-reducing major technology paradigm since DNA sequencing.

Newer models solve benchmarks for less $



The price of AI is falling faster than anything before it



stateof.ai 2026

Reasoning makes token price a poor proxy for the cost of an answer

- **Artificial Analysis measures task cost from the number and price of input, cache, reasoning and answer tokens consumed across its evaluations. The economic unit is the completed task, and Anthropic's frontier models have the highest measured task costs, reflecting both their token consumption and the prices applied to reasoning, cache and answer tokens.**



A dollar buys very different amounts of frontier benchmark performance

Across 12 of the original 13 vendors, the highest-index eligible model ranges from 8.4 to 57.6 AA Index points per task-dollar, a 6.9x spread reflecting scores, token use, inference effort and pricing.



AA Index v4.3.2 / task cost, 2026-10-02. Non-Flash, non-lightweight, no fallback.
Inkling cost unavailable; Anthropic uses Opus 5, which AA marks superseded.

Sell the work, not the tools?

As AI systems become more capable, the industry will increasingly value finished work over chats. But how will this change the business model of AI? As capability advances from Chat to Coding to Agent to Co-work to Autonomous AI, each level changes how the product is sold, from free chat and subscriptions to outcomes priced per completed task.



Vertical AI companies post-train open models past the frontier in their own domain

Frontier open Chinese models are handing application companies like Harvey, Cursor, and Mercor the opportunity to reduce costs and boost performance on the domains their customers care about.

- Harvey's post-trained GLM-5.2 runs in production at 54.8% lower cost per cell than Sonnet 5, and scores 0.903 on their Legal Review Table answer quality against 0.867 for Fable 5.
- Mercor post-trained Qwen3.5-397B-A17B on 1,928 expert tasks, raising overall Pass@1 on 480 held-out APEX-Agents tasks from 16.11% to 27.29%.
- In these settings, a company's focus on a knowledge work vertical enables them to build the best graded task environments with expert data.

Company	Open base	Reported result
Harvey document review	GLM-5.2	**0.903** answer score, ahead of Fable 5 at 0.867
Cursor software engineering	Kimi K2.5	**25x** more synthetic RL tasks than Composer 2
Mercor law, banking, consulting	Qwen3.5 397B-A17B	**16.11% to 27.29%** Pass@1 on held-out APEX-Agents (overall)

Production feedback guides improvements across the AI stack

Companies can start with frontier APIs to find product-market fit, then build their own evaluations and tools. Production feedback shows where to improve the system. Post-training becomes worthwhile when proprietary data and gains in quality, latency or cost justify taking control of the model.

- Failed tasks become repeatable tests with the context, tools and expert checks needed to judge success.
- Corrections, retries and execution traces reveal whether a failure came from missing context, a tool or the model.
- Improvements can change memory, tools, routing or model weights, with each change tested before deployment.



Agents now build and fix customer service agents, and the customer's staff approve

Customer service agents used to be built by the vendor's forward-deployed engineers, who turn a customer's policies into agent behavior, and fixed by teams reading transcripts. Vendors now sell agents that do both: staff describe changes in plain English and approve fixes the agent has already tested.

- **Build:** PolyAI says customers used Wren for 87% of changes they deployed in the week of 21 September, up from 52% in the week of 13 July.
- **Fix:** Decagon's Autopilot tests each fix on past conversations, then a person approves it. It beat certified Decagon staff on Decagon's own diagnostic benchmark, 93% to 83%.
- **Speed:** Decagon says engineering hours per voice launch more than halved in six months, and time to go live fell about 37%.

	Builds agents from	Tests a fix on	Reported result
Sierra Ghostwriter	SOPs, transcripts, whiteboard photos	Simulations	*None published*
Decagon Autopilot	Its building agent, Duet	Failing chat plus a golden set	**93% vs 83% for staff**
PolyAI Wren and Cortex	Plain English, SOPs and photos	Past and simulated chats	**87% of customer changes via Wren**
NiCE Cognigy	Claude Code, Codex or Cursor	*Not described*	*None published*

What training data is valuable? Execution traces and in-domain records

Labs need examples of how work gets done, not just finished answers. Expert-corrected action traces can improve agents, while brokers now pay companies for operating records such as procedures, CRM histories and project archives.

- OpenAI and Thrive reused expert-corrected tax-agent traces. Documents filed at ⩾75% accuracy rose from 25% to 86% within six weeks.
- micro1 offers $100k to $1M+ to license company procedures and records. Mercor says enterprise data partnerships can pay more than $10M.
- These are different assets: traces reveal decisions and corrections, while company archives supply domain context. Broker payment claims are company-reported.

	Execution traces	In-domain records
What it contains	Every step, tool call and expert correction of a real task	Private company records, or material written to order by paid experts
Why it is useful	Shows the decisions behind the answer	Covers a field with little public data
Example	Coding agent tool calls, customer support steps	Clinical notes, internal policies

Teaching AI is now generating billions of dollars in revenue

More and more RL environment companies are springing up thanks to a positive feedback loop drives demand: labs release models and invite community testing with evals and environments they create. These evals are hotly contested and observed because they expose strengths and gaps, so labs buy targeted data, improve models and release again, revealing new gaps...

Mercor	Handshake AI	micro1	Surge AI	Scale AI
$2B	**Nearly $1B**	**>$500M**	**$1.2B**	**Just under $1B**
Jun 2026	**Apr 2026**	**Sep 2026**	**FY 2024**	**FY 2025**
Gross annualized	Gross annualized · AI only	Annualized revenue	Full-year revenue	Full-year revenue
$75M · Feb '25 $500M · Sep '25 $2B · Jun '26	$100M · by Oct '25 $550M · Jan '26 Nearly $1B · Apr '26	$7M · early '25 >$300M · Apr '26 >$500M · Sep '26	$1.2B · FY '24	$250M · FY '22 $870M · FY '24 Just under $1B · FY '25

Medicines from AI-first drug discovery have reached Phase 3

What does it really mean for a medicine to be "made by AI"? The answer differs by company, so this table summarizes key assets and how AI was used. Two programs have reached Phase 3, with primary completion expected in 2028-29. Faster discovery has yet to establish higher clinical success rates.

Company	Medicine	The role of AI in the program	Current program status
Generate:Biomedicines	**GB-0895** antibody, severe asthma	ML-guided optimization reached 106 fM binding to TSLP, about 20x tighter than tezepelumab.	**Phase 3.** Two 786-patient trials of twice-yearly dosing. Primary completion estimated Dec 2028 / Jan 2029.
Insilico Medicine	**rentosertib** TNIK pill, lung fibrosis (IPF)	PandaOmics ranked TNIK first among kinases from omics and text data. Chemistry42 generated inhibitors.	**Phase 3.** 320 patients, 52 weeks, 47 sites in China. Estimated primary completion: Oct 2029.
enveda	**ENV-294** pill for eczema and asthma	Transformers pretrained on 1.2B mass spectra predict the structures of unknown molecules made by living organisms.	**Phase 2a.** Placebo-controlled eczema and asthma trials underway. Phase 1b: mean eczema severity fell 85% by day 42 (n=9, no placebo).
Recursion	**REC-4881** ex-Takeda MEK pill, polyposis	Deep learning on microscopy of APC-deficient cells ranked thousands of compounds by phenotype rescue.	**Phase 2.** Median polyp burden fell 43% at week 13 (n=12, no placebo). FDA path update due H2 2026.
Iambic	**IAM1363** HER2 pill, solid tumors	NeuralPLexer, a diffusion model, predicts drug-protein structures. Enchant predicts clinical endpoints.	**Phase 1/1b.** Partial responses in 28% of 18 pretreated patients at 960 mg a day or more (Oct 2025).

Note: Enveda status company-confirmed Oct 7, 2026. Other statuses checked Sept 19; trial dates updated Sept 24.

Muse brings Zuckerberg's "personal superintelligence" vision to market

In July 2025, Zuckerberg promised "personal superintelligence for everyone": AI that helps people pursue their own goals. Muse gives each user a persistent cloud computer to act across apps. Commerce and enterprise turn that vision into services people and businesses can pay for.

- **Consumer pull:** 2.8M downloads in two weeks and No. 1 on US app charts, after Llama 4's poor reception and Meta AI's earlier app struggles. Meta shares rose >11% on September 21.
- **Commerce:** A step toward our 2025 prediction. Stripe Link enables checkout at 1M+ merchants, and Shopify, Walmart, Shop Pay and PayPal partnerships connect discovery to payment.
- **Enterprise:** Ex-MongoDB CEO CJ Desai will sell APIs, coding tools and business agents. Inference demand helps monetize Meta Compute, and direct compute sales are under consideration.

Muse Charm: a Tamagotchi-like device previewed at Connect. Muse is also coming to Meta's AI glasses.

AI shopping referrals are growing quickly and converting at higher rates

AI assistants help shoppers compare products and narrow their choices before visiting a retailer. While direct AI referrals remain a small share of ecommerce traffic, their rapid growth and higher conversion rates suggest an increasingly valuable source of customers.

- Similarweb reports 203% annual growth in AI referrals, which still account for only 0.4% of retail ecommerce visits.
- Shopify's AI-referred product-page visitors converted about 80% more often than organic-search visitors in Q2 2026.
- Profound finds that retail brand mentions in ChatGPT were followed by 38% more site visits than the forecast baseline over seven days.

AI vs. non-AI purchase conversion on US retail sites
Relative difference, measured by Adobe Analytics



Cloud backlogs are growing, and neocloud revenues are ramping even quicker

Big cloud's reported backlog reached $1.69T in June 2026, while CoreWeave's quarterly revenue reached $2.58B.

Big cloud: contracted future revenue ($B)



Quarterly revenue ($B)



Note: Backlog includes non-AI business. Alphabet added shorter contracts in 2026.

Neoclouds have contracted >15GW of AI compute...and are racing to get it live

The lag between contracting compute and getting it live is down to atoms: finding the site, gaining approvals, building, energising, and installing equipment before customers can start running jobs. For example, CoreWeave ended Q2 2026 with 1.5GW of active power against 4.2GW of contracted, and targets more than 8GW by 2030. On pricing, immediacy commands a premium: short-duration capacity clears ~$40 to $50M per MW versus ~$20 to $25M on multi-year deals.

Data as of Q2 2026.

Crypto miners are pivoting from further behind: 5.6GW contracted vs. 900MW live

Applied Digital and Core Scientific (whose $9B acquisition by CoreWeave was rejected by the board in Oct-25) lead on contracted power with 2.5GW, of which 25% is live. The AI power is net-new build on grid interconnects and land these companies already held as Bitcoin miners. Several are converting old mining sites and shrinking Bitcoin to free the power. The tenants concentrate into a short list: CoreWeave, Fluidstack, AWS, and Microsoft.



Data as of Q2 2026.

AI takes most capex as hyperscaler budgets head above $1T annually

Exponential View estimates AI accounts for 64% of seven cloud companies' planned 2026 capex, or about $563B. Separately, Bloomberg consensus for five hyperscalers forecasts total capex above $1T annually from 2027 through 2030.

Estimated AI share of capex (%)

2026: ~$563B AI / $879B total



Source: Exponential View, Sep 27. Adds CoreWeave and Nebius to the five hyperscalers at right. Modeled AI share.

Total annual capex forecasts hit $1T

Annual total capex ($B)

Source: Vanguard / Bloomberg, Jul 31. Alphabet, Amazon, Meta, Microsoft and Oracle. E = forecast.

AI build-out draws on chipmaker guarantees and hyperscaler equity

NVIDIA and Broadcom expanded guarantees for infrastructure funded by outside investors. Customer defaults could cost them both sales and guarantee payments, though NVIDIA argues independent underwriting and reusable hardware reduce this risk. Separately, hyperscalers are selling equity: Alphabet raised $49.6B net in June, including $10B from Berkshire, for corporate uses including AI infrastructure and compute.

2026 arrangement	Financing and chipmaker support	Risk retained by the chipmaker
NVIDIA / OpenAI and SB Energy	Up to $105B of guarantees for specified lease and power payments	Covers specified default shortfalls after recoveries. Effective as leases commence.
Broadcom / Apollo and Blackstone	$35B financing, with up to $29B of Broadcom lease backstop exposure	Covers part of default losses after recovering value from the AI racks.
NVIDIA / six financial institutions	>$500B financing target. Potential residual-value support up to 25% per selected deal.	May absorb shortfalls in the infrastructure's future asset value.

Residual value guarantees spread from Meta's data centers to the chipmakers

A residual value guarantee promises lenders a minimum resale value for a data center or its chips. The debt is held in a separate company that owns the asset (SPV), so it is off the balance sheet of the guarantor. Morgan Stanley designed the structure for Meta's Hyperion campus in October 2025, and it has become popular since.

- Four guarantees issued in under 12 months sum to $175B: Meta $41B, Broadcom $29B and NVIDIA $105B.
- Guaranteed debt prices just 100-150bp above the guarantor's own bonds, which let Hyperion raise a whopping $27B.
- NVIDIA records no liability until OpenAI's Ohio leases begin in 2028, and the campus will run only NVIDIA hardware for 20 years.

Hyperscalers and chipmakers hold over $3T of commitments off their balance sheets

Morgan Stanley counts more than $3T of off-balance-sheet commitments and credit support across seven hyperscalers and chipmakers. Most are purchase commitments and leases on data centers that have not opened yet. These are contracted future payments rather than borrowings, so they sit outside reported debt.

- Google carries the most at $890B, with $707B of it in purchase commitments, while Microsoft and Oracle are mostly leases.
- S&P forecasts Amazon's adjusted debt at 1.6x EBITDA in 2027, above its 1.5x downgrade threshold, and Oracle's at 4.4x against 4.5x.
- S&P adds a guarantee to debt only where it exceeds a stressed sale value, a gap it calls "closer to zero most of the time."

Off balance sheet and contingent commitments by company

GPUs now cost more than they did at their lows

On-demand pricing for 10 GPU SKUs bottomed across seven quarters between Q3 2024 and Q1 2026, most of them in Q3 2025. Since then the weakest bounce was +7% (A100) and the strongest +60% (MI300X), with the average +30%. Even the nine-year-old V100 now costs 43% more than in Sept-25.

† Three chips whose low is also their first month in the index, their price never fell during the observed window.

A100 and V100 remain rentable six and nine years after launch

How long GPUs can earn is central to the depreciation debate. September 2026 median posted rents are $1.76/hour for A100 and $0.95 for V100. Older generations remain commercially available, but list rates alone cannot establish profitability or the right accounting life. Those depend on paid utilization, operating costs and when each asset entered service.



Six years after launch, A100 still leads NVIDIA chip mentions in AI papers

Launched in May 2020, A100 remains the NVIDIA chip whose use is reported most often in open-source AI papers, ahead of H100 and H200 combined. A new generation does not end the previous one's research use. The 2026 counts include a projection for the rest of the year.

- A100 reaches 14,707 papers in the 2026 estimate: 96% of its 2025 count and 85% of its 2024 peak.
- Hopper (H100 and H200) more than doubles to 9,931 papers. Data center Blackwell reaches 902, still far behind A100.
- This shows lasting research use. Paper mentions do not measure fleet utilization, rental income or profitability.

AI papers citing each NVIDIA chip (others in gray)



stateof.ai 2026

AI buyers are outbidding the grid for the machines that make electricity

GE Vernova, Siemens Energy and Mitsubishi Heavy Industries have backlog orders worth 220 GW of large-frame gas turbines against a global build rate of 60-70 GW/year. They're requiring up-front cash deposits - $87B worth as of 30 June '26 - to hold a future manufacturing slot and are credited on delivery against the purchase price.

- GE Vernova expects its gas equipment backlog and slot reservation agreements to be at least 125 GW by EO26. Its own output capacity is 20 GW a year, reaching 30 GW in 2030. Data center orders passed $5B year to date, more than double all of 2025. Chart shows GEV gas turbines orders vs deliveries.
- Siemens Energy can deliver 15-16 GW in 2026 vs. demand for 69 GW, with longer than 3 year lead times.
- Mitsubishi's orders taken last quarter are scheduled for delivery in 2028 to 2030.
- Turbine prices are up 195% since 2019, which is driving new vendors like Boom Supersonic to repurpose their jet turbine towards energy production for data centers.

Retired coal sites are being rebuilt as gigawatt-scale gas campuses for AI

AI is reversing coal's retirement plan: the US had planned to retire 8.5 GW worth of coal capacity by EO2025, but only ended up retiring 2.6 GW worth. The rest was pushed out into the future or cancelled outright. The reason? Developers are buying the grid interconnection, substations, water and permitting that's already in place to skip multi-year long queues for new connections.

- To be clear, AI isn't exactly saving coal plants. But when load forecasts increase, data center agreements feed the utility's resource plan, and a resource plan that is short of capacity can no longer afford retirement.
- Homer City in Pennsylvania hosts the state's largest coal plant that used to generate 2 GW. It was demolished in 2025 and is now being redeveloped with $10B into a 4.4 GW natural gas-powered site with GE Vernova turbines to power a large-scale AI data center. While there is no anchor tenant, Amazon is reportedly in talks.

Five American clusters, each larger than those in the European Union combined

The EU-27 holds 79,657 H100-equivalents of installed AI compute, or 5% of Epoch's documented sample excluding China. One phase of xAI's Memphis site holds 3.5x that.

- xAI's Colossus Memphis Phase 3 alone holds 3.5 times the entire EU total.
- Excluding China, the EU-27 holds 5% of documented AI compute vs. 80% in the US.
- Europe's largest machine, JUPITER at Jülich, would not make the American top-10.
- Norway has more installed AI compute than France. The UK has less than Finland



Four US hyperscalers will spend $733B in total capex in 2026, Europe commits €1B

The US build-out is led by hyperscalers with large balance sheets. Europe's gigafactory push relies on public procurement to draw in private capital. The €1B EU commitment is an initial program contribution, while $733B is US hyperscalers' total annual capex, not an AI-only figure.

- The big 4 spending grew by $349B in 2026 alone as they all raised guidance.
- That increase on its own is more than 10x the entire EU program.
- Bidding opened in July 2026 and will close in mid-November 2026.
- First construction is due for 2027 for operation in 2028.



ASML sold six more EUV machines in 2025 than 2021, at a 61% higher average price

ASML's EUV system sales rose from 42 in 2021 to 48 in 2025. Over the same period, average revenue per machine rose from about €150M to €242M, a 61% increase. Higher prices and the changing product mix helped revenue grow faster than the number of systems sold.





Leaders can't be choosers: labs assemble diversified compute portfolios

Frontier labs spread compute across NVIDIA, AMD, TPUs, Trainium and custom chips. Announced gigawatts include plans and signed agreements, with overlapping deals that cannot be summed into a contracted or operating total.

- OpenAI committed to 2 GW of Trainium and 0.75 GW of Cerebras, alongside its 10 GW Broadcom roadmap.
- Anthropic names 5 GW of Google TPUs and up to 5 GW from AWS, plus NVIDIA capacity through Azure and SpaceX.
- The portfolio now extends to CPUs: Anthropic's September Akamai agreement commits $11.6B over seven years.



NVIDIA faces different challengers in training and inference

NVIDIA's challengers span established chip vendors, in-house silicon and independent AI chip companies. Their deployment ranges from large production clusters to first shipments and chips still in development.

Commercial platforms

AMD
Instinct ● ●

intel.
Gaudi ● ●

tenstorrent
Blackhole ●

In-house silicon

Google
TPU ● ●

aws
Trainium ● ●

Microsoft
Maia ●

Meta
MTIA ● ●

OpenAI
Jalapeño ●
Deployment planned

Independent AI chips

cerebras
WSE-3 ● ●

sambanova
RDU ●

d-Matrix
Corsair ●

Etched
First rack ●

FURIOSA
RNGD ●

rebellions_
Rebel100 ●

MATX
In dev. ● ●

FRACTILE
In dev. ●

Euclyd
craftwerk ●
In dev

OLIX
DX-1 ●
In dev

China alternatives

HUAWEI
Ascend ● ●

Cambricon 寒武纪
MLU ● ●

Kunlunxin
P800 ● ●

● Training ● Inference

Google's Ironwood serves Qwen at lower modeled cost than B200 and B300

Google is opening its TPU software stack to models beyond Gemini. SemiAnalysis tested Qwen3.5-397B on Ironwood using TorchTPU, which lets PyTorch models run on TPUs. At the same generation speed, its estimated cost per token was lower than NVIDIA's B200 and B300.

- At 100 output tokens per second per user, Ironwood costs an estimated $0.181 per million input and output tokens, versus $0.222 for B200 and $0.276 for B300.
- The test uses FP8 precision, 8,000 input tokens and 1,000 output tokens, with input processing and generation on the same hardware. Note that these are ownership-cost estimates, not API prices.
- NVIDIA can regain the lead with FP4 precision or separate hardware for input processing and generation. TorchTPU still needs broader model support and serving optimizations.

But just as rivals catch Blackwell, NVIDIA moves the goalposts again

Google's results show that alternatives to NVIDIA can compete on inference cost. But the comparison keeps changing: SemiAnalysis's early Rubin tests show another substantial improvement over Blackwell on workloads that reproduce how agents use models.

- Running DeepSeek V4 Pro at a matched response speed of 100 tokens per second, Rubin delivers 2.1x the total toker throughput per megawatt of the strongest tested GB300 configuration.
- At that speed, GB300 reaches 28.5 million tokens per second per megawatt with SGLang, versus 21.1 million wi TensorRT-LLM.
- This suggests that winning workloads from NVIDIA means competing with its next generation while improving your own software. Although Google now has credible results, NVIDIA has hardly stopped to admire them.



Better systems help Huawei compete, but memory still limits supply

Huawei's Atlas 950 roadmap connects up to 8,192 chips, while software is being tuned for Chinese models. Its chair says Ascend has surpassed NVIDIA in China, while acknowledging NVIDIA's market share is hard to measure. Supply remains tight and H200 sales in China require both U.S. licenses and Chinese approval.

- SemiAnalysis's June 2026 analysis found launch-day DeepSeek V4 support and live API serving on Ascend. Huawei's software overlaps computation and data transfers to keep chips busy.
- Memory limits deployment: reports that DeepSeek's planned order of at least 160,000 950DTs could take over a year to fill. Other reports card quotes up 20-50% in two months.

Memory and access for Chinese buyers

Chip	Memory	Bandwidth	China access
Huawei 950DT	**144 GB**	**4 TB/s**	**Early use reported, but supply constrained**
NVIDIA H200	141 GB	4.8 TB/s	Approved buyers with limited deliveries

Despite competition, NVIDIA remains the default chip in AI research papers

Last year, chip mentions in open-source AI papers fell for the first time in six years. Zeta Alpha's 2026 projection, based on counts to 1 September, has them rebounding: 44,134 papers cite NVIDIA, up 9.5%. That is about 90% of all accelerator mentions, the same share as in 2025.

- AMD mentions grow fastest, up 62% to 406 papers, followed by Huawei's Ascend, up 52% to 208.
- Apple silicon rises 43% to 1,062 papers, nearly level with Google's TPU.
- TPU mentions, however, fall for a second year, to 1,120 from a peak of 1,702 in 2024.

AI papers citing each chip family (log scale)



Jensen Huang writes in defense of open-weight models

A week after Moonshot's open-weight Kimi K3 topped an LMArena board and reports circulated that the White House was weighing conditions on US companies that use Chinese models, Jensen's goes direct on X to publish an open letter, "Open weights and American AI leadership". Huang's version of Jevon's Paradox: "Whenever there's more use, you'll have to sell a lot more NVIDIA computers."

- The letter launched with 25 signatories and now lists 235, including OpenAI, Google, Meta, Microsoft and AMD. Anthropic is absent.
- It asks Washington to avoid "premature restrictions on open models" and not to conflate distillation with misappropriation.
- NVIDIA has added about 860 popular repos on HF since Jan 2025, nearly twice runner-up Alibaba.



Cumulative new HF repos >500 downloads by org since Jan 2025



Then, NVIDIA commits almost $20B to open weight AI in two weeks

NVIDIA committed about $19.9B across two deals: $12.93B for Hugging Face and $7B in Poolside licensing and equity. One brings the distribution platform for open models, while the other brings a model factory and research staff. Hugging Face's acquisition is expected to close in H1 2027.

Hugging Face

$12.93B acquisition, agreed 3 September 2026
Hugging Face keeps its brand and stays open to every model, cloud and chip. Close expected in H1 2027.

NVIDIA gets distribution and mindshare
The town hall for open AI: 18M users share 3M models, and 200,000 companies use it to find and deploy them. Every open lab launches there, from Qwen and Kimi to NVIDIA's own Nemotron.

$6B license plus $1B of equity, 21 August 2026
Non-exclusive licensing deal and $1B investment at $12B pre-money valuation. Poolside founders don't join NVIDIA.

NVIDIA gets a model factory and team
The Model Factory trains and tests Poolside's open-weight Laguna coding models. NVIDIA offered jobs to 109 staff, while fewer than 115 engineers and researchers built Laguna.

NVIDIA buys, funds, and open sources the AI stack

NVIDIA participated in 84 AI funding rounds this year, roughly twice it's 2024 total, helping finance demand for its own chips. NVIDIA's investments and acquisitions span the AI stack to complement its open model releases and optimizations of other labs' models for its hardware.



Note: left tile data from 16 Sept 2026 (Dealroom) and right tile data from 24 Sept 2026 (Hugging Face)

One year on: Waymo tripled to 220M rider-only miles and serves 500k rides a week

In last year's report, Waymo had logged 71M rider-only miles through March 2025. Waymo's safety hub now shows 220M through March 2026, over 4M a week, with 94% fewer serious-injury crashes than human drivers on the same roads. Paid rides doubled to 500k+ a week across 14 US cities, with a stated target of 1M a week by EO26.

- Meanwhile, Tesla's paid robotaxi miles reached 2.4M by June 2026, adding ~0.9M in Q2 and the same in Q1.
- Waymo added Miami, Dallas, Houston, San Antonio, Orlando, Nashville, Denver, San Diego and Tampa since last year's report.
- In the UK, Waymo has tested in London since April and targets a Q4 driverless launch. Wayve and Uber now offer paid, supervised autonomous rides in London, with a licensed driver onboard.
- In China, Baidu's Apollo Go fell from 3.2M driverless rides in Q1 to around 1M in Q2, citing "operational adjustments" on regulatory grounds.

Waymo rider-only miles



Waymo paid rides per week



Data center developers are deploying robots to speed up construction

Today, robots are fabricating components, printing layouts and drilling anchors for data centers. More recent dexterous systems are also being used for equipment fit-out. While evidence of faster completion of entire facilities remains limited so far, contractors and suppliers report gains on specific tasks that we highlight below:

Fabricate

HireBotics Tate.

~12x per-welder throughput for structural assembly

Lay out

DUSTY ROBOTICS align

784 hours saved on layout supporting 2,304 racks

Drill

AUGUST ROBOTICS DEWALT

90k+ holes drilled with 99.97% accuracy in depth and location

Fit out

WATNEY

Reported operations in hyperscaler DCs

Physical AI companies will clean your home...for data

Human labor is now a loss leader for robot data. Germany's microagi offers Shift, a service to clean your NYC apartment for free while its operator's headcam records the entire thing. Meanwhile, Figure's Index has paid $15M to 264k people in 100+ countries to film daily chores from a headset, producing 16M videos toward what it calls the world's largest physical dataset.

microagi

FIGURE

Unitree's rapid growth is already profitable

Unitree grew revenue 333% to approximately $238M in 2025, earning $39M in net profit. Its 16% group net margin approached FANUC's 20%, despite operating at a much smaller scale. Humanoid sales rose from 412 in 2024 to 5,215 in 2025 (12.7x), while average price fell 36%, from RMB260,400 to RMB166,400. Humanoid gross margin fell from 69% to 63%.

Company	Main business	Revenue growth	Net margin
UNITREE	Humanoids, quadrupeds and components	333%	16%
UBTECH	Humanoids, education and consumer robots	53%	-39%
FANUC	Industrial robots, automation and machine tools	8%	20%
YASKAWA	Industrial robots, motors and drives	1%	7%

Note: Group results; fiscal years and product mixes differ.

The physical AI stack is powered by billions and billions of venture capital dollars

There's never been a more vibrant robotics research environment in the last decade. And this has translated into huge capital flows in 2026 for robotics labs, humanoid makers and autonomy companies that would have been unthinkable a few years ago, with hyperscalers, carmakers and sovereign funds backing up the truck.

- Skild AI raised $1.4B at >$14B valuation, led by SoftBank with NVIDIA, tripling its valuation in seven months, and Apptronik closed a $935M Series A with Google, Mercedes-Benz and John Deere.
- Wayve raised $1.2B at $8.6B with Uber committing milestone capital that takes the total to $1.5B, and Rivian's spin-out Mind Robotics raised $500M at about $2B four months after its seed.
- Humanoid financings included NEURA (up to $1.4B), XPENG Robotics (>$900M), Galbot (~$362M, per Caixin), ROBOTERA (>$200M), LimX (nearly $200M) and Humanoid ($152M).



Chinese humanoid companies attract slightly less than two-thirds of global funding

Dealroom tracks 18 humanoid companies in China, 18 in the US and 17 in Europe, yet China leads in funding. US restrictions on new foreign-made robot approvals could redirect demand toward domestic production, while complicating access to Chinese hardware used by American researchers.



Private capital is only interested in AI companies, and largely American ones

GenAI takes $5 of every $6 in the year's biggest rounds

The 15 largest AI VC rounds of 2026, to 16 Sept.

US companies take about three of every four AI dollars

VC funding into AI companies, by company HQ



Private AI valuations have risen fast, very fast

Across the companies shown, estimated valuation-doubling times range from 3.5 to 13.3 months. These historical fits describe fundraising marks, not a law that valuations must continue to follow.



AI company revenue multiples range widely, even among the largest labs

The latest marks shown range from 15x for Anthropic to 250x for xAI, with OpenAI at 21x and Cohere at 83x. Reported and estimated revenue figures are mixed, so the chart is a snapshot of market pricing rather than a like-for-like valuation rule.



The labs are raising capital at the scale of hyperscale capex

Amazon, Alphabet, Microsoft and Meta guide to $733B in 2026 capex, up 79% from $410B in 2025. OpenAI and Anthropic have announced $122B and $95B of funding, respectively, in 2026.



Capex growth: 2026 guidance vs. 2025

Amazon	**+71%**
Alphabet	**+119%**
Microsoft	**+48%**
Meta	**+90%**
All four combined	**+79%**

Gulf investors participate in some of the largest American AI rounds

- **Dealroom tracks who participates in financing rounds. MENA investors took part in rounds representing half of AI funding dollars in 2026. This counts the full value of those rounds, not the amount of capital supplied by Gulf investors**





Mega rounds continue to eat the lion's share of private AI company raises

94% of all dollars invested into companies in 2026 were part of $250M+ rounds, up from 10% in 2022...



dealroom.co *Note: The 2015 spike is one deal, Alibaba's $1B investment into Alibaba Cloud.*

China's AI IPO wave has delivered big gains and rich valuations

Share-price gains imply ~$548B of enterprise-value uplift since IPO at constant capital structures, 87% coming from gains posted by DRAM company, CXMT. At September 18 prices, the five names trade at 19-189x trailing revenue, the highest multiple being held by Z.ai

- The IPO cohort spans model developers, GPU designers and CXMT's DRAM business.
- Micron and SK hynix also sell NAND storage and high-bandwidth memory, so their product mix differs.
- US labs use older private-round equity values and annualized sales. These gray bars give context but are not like-for-like public multiples.



Implied EV uplift: ~$548B
87% from CXMT



Public: EV / trailing revenue.
*US labs: equity / annualized revenue.

Is the ROI on NVIDIA better than its Western competitors? Yes.

Across modeled rounds in eight Western challengers, $17.3B invested produces $54.9B of estimated NAV plus $7.7B of distributions (3.6x), versus $80.6B in NVIDIA (4.7x). Recent mega-rounds, invested after NVIDIA's huge run-up, compress the multiples: $11.7B of 2026 funding pulls NVIDIA from 12.2x for older cohorts to 4.7x overall.



As of 25 Sep 2026. Modeled rounds, not all funding. Dates, valuation assumptions and coverage gaps are in the linked model.

Chinese NVIDIA competitors, however, produced higher ROI

The pattern reverses in China: $12.4B across modeled rounds in six challengers produces $108.5B of estimated investor NAV (8.8x), versus $91.6B (7.4x) if the same dollars bought NVIDIA on each funding date. Returns follow investors' shares through dilution and IPOs. Unpriced early rounds are excluded symmetrically.



As of 25 Sep 2026. Modeled rounds, not all funding. Dates, valuation assumptions and coverage gaps are in the linked model.

Leverage amplified the reversal in the AI memory trade

Korean retail investors returned to memory stocks with margin loans and leveraged ETFs. When the trade reversed in July, forced liquidations at 10 brokers reached ₩43.9B a day, 13x a year earlier. The same memory shock hit leveraged institutional investors.

- Retail bought ₩8.9T of 2x ETFs in four weeks, alongside record ₩37.3T margin loans. Leveraged SK Hynix ETFs lost 67-69% in July.
- The Kospi fell 22% that month. The chart shows daily forced liquidation value and affected accounts at 10 brokers.
- The FT ranks Situational Awareness's reported $35B July loss above Archegos and LTCM in its selected historical comparison.



The IPO window is thawing while M&A picks up with $B+ deals

AI exits are on pace to beat 2025 by about a fifth

Number of AI exits by type. 2026 is year to date, to 16 Sept.

The IPO window has reopened and M&A is following

Value of AI exits by type. The 2012 spike is Meta's $104bn IPO.

Big tech found a way to buy teams without buying their employer

29 deals, and the newest ones buy nothing but people

By what the acquirer actually took. 2026 is to 16 Sept.



OpenAI has done a quarter of them

Licence-and-hire deals by acquirer. 2026 is to 16 Sept.



Section 3: Politics

Welcome to the era of Super Intelligence, Superintelligence, or just SI...

- **"No one knows what it means, but it's provocative. It gets the people going."**

Tech executives in 2025

Trump signs the Super Intelligence Executive Order in 2026

Washington has flexed its control over frontier AI

- **Washington need not own frontier labs to control model access. US export controls halted Fable and Mythos in June, with Fable returning in July. In September, Politico reported a White House request for US review before OpenAI and Anthropic shared new models with UK testers. Access had not ended across the board: Britain's AI Security Institute tested GPT-6 Astra before release earlier that month. As we wrote on Air Street Press on 22 June, *"Europe cannot rent its way to AI sovereignty: When Washington can disable a model overnight, the question is not whether AI is safe but who controls it."***

June 12: Blocked

Scoop: Trump admin blocks foreign access to Anthropic's most powerful AI

July 1: Fable returns

Trump administration lifts restrictions on Anthropic's Claude models after cybersecurity alarm

Anthropic vs. US Government: who defines the limits of AI usage in defense

The labs' courtship of the Pentagon has exposed a critical question: can an AI lab set limits on the military's use of its AI systems? Anthropic refused domestic mass surveillance and fully autonomous lethal weapons. The government treated its objections as grounds for exclusion, and the fight went to court. Anthropic overturned one designation, but a September appeals ruling upheld its exclusion from the Pentagon's supply chain.

- US Secretary of War, Pete Hegseth, considered forcing Anthropic's cooperation under the Defense Production Act, then labeled it a supply-chain risk. Essential supplier or security threat?
- Officials kept pursuing a contract and discussing Mythos cooperation after the designation. The California court noted the contradiction.
- On August 27, a California court found unlawful retaliation and set aside the 10 U.S.C. §3252 designation. On September 25, the D.C. Circuit upheld the separate 41 U.S.C. §4713 procurement exclusion.

Frontier AI goes live in US military operations

Frontier AI now supports live US military operations, from a raid in Venezuela to the war in Iran. The Pentagon describes AI as supporting human judgment. CNN's reported near miss involving a Chinese ship shows how false AI-generated intelligence can still reach an operational plan.

Claude in the Maduro raid

Axios reports Claude was used during the raid that captured Nicolás Maduro. Its precise role was not confirmed.

Grok within Maven

The Pentagon says Grok-enabled Maven workflows helped US forces deploy over 2,000 munitions at 2,000 targets within 96 hours.

Maven at campaign scale

The Pentagon says Palantir's Maven Smart System supported a campaign hitting 13,000 targets in 38 days.

A near miss at sea

CNN reports an AI error falsely linked a Chinese ship's cargo to nuclear weapons. US troops prepared to board before officials caught the error.

Note: Overlapping events, not to scale; Grok's 96-hour interval is undated.

Iran turned US commercial cloud infrastructure into an explicit military target set

On March 1, Iranian drones directly struck two AWS facilities in the UAE. A nearby strike damaged AWS infrastructure in Bahrain. Iran then mapped 29 technology facilities as targets, separately named 18 organizations "legitimate targets," and threatened Stargate UAE. July brought another claimed attack in Bahrain, with satellite-observed damage but no AWS confirmation.

Outside the US and China, 67 countries have sovereign AI projects

CNAS tracks 184 government-backed AI projects in 67 countries outside the US and China, up from 18 announced in 2023. Their disclosed budgets total about $84B with the UAE and Japan accounting for nearly two-thirds, mostly via Stargate UAE and a national foundation model push.

Sovereign AI projects tracked by CNAS, cumulative





Selected sovereign AI program pledges total about $138B



Note: Program pledges, not spending. CNAS's ~$84B covers disclosed project budgets in a different country set.

NVIDIA earned over $30B from sovereign AI in FY2026

Governments building domestic AI capacity still depend on US suppliers. CNAS names NVIDIA on 53 sovereign infrastructure projects, versus 18 for HPE, the next vendor. HUMAIN's live Saudi cloud shows AMD is winning business too.

- Planned NVIDIA deployments include Kazakhstan's 100,000-GPU cluster, Japan's 27,500-GPU Noetra factory and HUMAIN's up to 600,000 GPUs across Saudi Arabia and the US.
- Saudi delivery is starting: HUMAIN and its partners report a live AMD cloud since August 2026, without disclosing operating MW, GPU count or customer names. More AMD capacity is due from H2 2027. Oxagon's first 100MW is targeted for 2028.



Note: CNAS, June 2026. Projects may name multiple vendors.

Korea is going big on funding domestic AI and building a market for it

Korea's 2026-2028 AI strategy aims for global top-three status. Its commercial logic connects local models, engineering skills and computing capacity with customers for a competitive inference industry.

Domestic models

Open weights, local expertise

LG, SK Telecom and Upstage advanced in the model contest after open-weight releases.

Inference capacity

₩9.9T AI budget for 2026

At least 50,000 government-led GPUs targeted by 2028, alongside domestic AI chips.

Universal access

Free AI services due in 2026

SK Telecom, Kakao and KT won contracts for free AI on existing consumer platforms.

Engineering skills

Model building develops talent

Training and optimizing models builds skills that can make local inference providers more capable.

Domestic demand

Government as first customer

Procurement and adoption vouchers help domestic model and agent firms win business.

Local opposition

AI ambition meets NIMBYism

Resident opposition has delayed projects, while Seoul districts push stricter siting rules.

Governments are funding compute access for domestic AI developers

Europe plans gigafactories; the UK and India allocate compute access to domestic developers. None of the three programs reports measured usage. Planned capacity, requested hours and approved allocations describe different stages of delivery.

European Union

Up to seven gigafactories backed by public procurement

TARGET: AROUND MID-2028

Early 2027 selection + up to 18 months

Capacity: up to seven sites, targeting mid-2028.
Funding: up to €10B public seeks at least €20B private.
Usage: not reported.

United Kingdom

SOV/AI announces doubling of its startup compute offer

>3M GPU-HOURS ALLOCATED

Six companies in the initial cohort

Allocation: over 3M GPU-hours.
Demand: 67M GPU-hours requested from over 200 applicants.
Usage: not reported.

India

Subsidized compute access through commercial providers

9.318M GPU-HOURS APPROVED

237 projects • August 2026 update

Allocation: 9.318M GPU-hours approved for 237 projects.
Supply: 15 commercial providers.
Usage: not reported.

You either die trying to get to the frontier, or live long enough to serve inference

Europe's major shot at frontier AI, Mistral, has pledged 1GW of European compute by 2030 to serve its own and Chinese open-weight models. Its new Large 4 Preview trails Opus 5.5 by 20 points on Artificial Analysis's current index.

- Amadeus, ASML, Capgemini, Caisse des Dépôts and CMA CGM fund the build and can recoup spending through training, inference or fine-tuning.
- Microsoft announced in July 2026 that it would be an anchor customer for thousands of Vera Rubin chips.
- Large 4 Preview scores 38, up from Medium 3.5's 14, versus 58 for Opus 5.5 and 39 for DeepSeek V4.1 Flash.



Note: Artificial Analysis v4.3.2, 2026-10-07. Large 4 is a Preview. Selected models; higher is better.

Europe could bargain for frontier AI access with sites and chips

Europe's influence over AI rules has not secured access to the most capable models. An independent September strategy proposes trading data center sites for access to foreign frontier AI. Britain is pursuing similar bargaining power by backing new inference chips.

- The proposal offers powered sites and fast permits for model access on par with the provider's home market, using local data centers to enforce the deal.
- The UK's £150M commitment to buy novel inference chips could help British suppliers grow and give the UK more bargaining power with foreign labs.
- Neither route guarantees access: foreign governments can restrict it, and chips only create leverage if they are hard to replace.

Proposed European access bargain



One strategy prices a European frontier lab at €790B over three years

An independent European AI strategy estimates €790B over three years to build a frontier lab, with a €445B-€1,040B range. This is a mostly publicly financed scenario, not EU policy or a guaranteed cost of catching up. Staffing and coordination remain additional execution challenges.

- The authors budget €529B for accelerators and facilities, plus €105B to rent compute while clusters are being built up.
- Public ownership at founding comes with technical independence and durable coalition backing. Governments must agree when to stop funding it.
- Building a lab competes for sites and chips that could secure foreign model access. The plan still budgets €3B for foreign coding agents.



Europe's data center ambition is hampered by significantly more expensive energy costs

Business power benchmarks range from $0.085/kWh in Finland and $0.086 for US industry to $0.373 in the UK, while China's indicative tariff is $0.109. Periods and tax treatment differ, and these retail benchmarks are not matched data-center contracts, but directionally point to severe cost advantages in the US, China, and Nordics.

2025 retail electricity benchmarks ($/kWh)

What a power premium costs

Consider a 1 GW data center site that requires continuous load.

If the cost per kWh increases by X cents, how much extra cost is that per year?

+$0.01/kWh = $87.6M/year
+$0.05/kWh = $438M/year

China uses cheap power to favor domestic AI chips

Power subsidies can change which accelerators make economic sense. The FT reported that some provinces offer larger discounts to data centers using Chinese chips, helping offset their higher energy costs. The incentive links the western computing buildout to Beijing's push for domestic suppliers.

- Gansu, Guizhou and Inner Mongolia reportedly offered electricity discounts of **up to 50%** for large data centers using domestic chips.
- Facilities using foreign chips such as Nvidia's were **ineligible** for these enhanced subsidies, according to the FT's sources.
- China's April 2026 AI+ program also directs provinces and central state-owned enterprises to develop industry datasets, models and applications across 20 sectors.

Western hubs serve eastern demand



MERICS: eight hubs. Arrows show computing flows.

China's data-center capacity is projected to exceed EMEA's by end-2026

SemiAnalysis uses filings and construction disclosures for 1,000+ Chinese facilities across 60+ operators, inferring missing MW from racks, investment or floor area. For 5,000+ sites elsewhere, it uses property records, permits, power data and satellite imagery. Capacity covers AI and conventional computing.



US chip licenses deliver limited H200 sales to China

US export licenses reopened a route for NVIDIA's chips to China, but Beijing still restricted sales. In the quarter ended July 26, 2026, licensed H200 shipments contributed less than 1% of NVIDIA's Data Center revenue. Required US inspections also triggered a 25% import tariff that NVIDIA says it could not pass on to customers.

H20 restrictions	H20 licenses issued	Domestic-chip push	H200 route opens	Sales remain limited
US requires export licenses. NVIDIA takes a $4.5B charge for inventory and purchase obligations.	US reverses course. Officials expect 15% of licensed sales, with no regulation yet codifying it.	Reuters reports domestic-only chips for new state-funded data centers. Geographic scope is unclear.	H200 / MI325X get case-by-case review. Limited H200 licenses begin in February, with a 25% inspection tariff.	Licensed H200 shipments: <1% of Data Center revenue. H200 charge: $0.4B in the first half of FY2027.

Note: Selected policy milestones; spacing is not to scale.

China starts controlling export of know-how and reverses the Manus sale

Where the US guards chips, China treats AI know-how as a strategic asset. With the forced unwinding of Meta's acquisition of Manus, Beijing has shown that it is serious about keeping IP and talent at home.

- **Companies:** In April 2026, China reversed Meta's ~$2B acquisition of AI agent company Manus, even though Manus had moved its headquarters to Singapore.
- **IP:** Since July 2026, sending staff or technical help abroad needs approval if controlled tech is involved. Frontier LLMs aren't on that list yet, but curbs on model weights are under discussion.
- **Talent:** A September 2026 rule enables Beijing to issue exit bans for people deemed a potential threat to national technology security.



Washington and US labs treat alleged Chinese distillation campaigns as a security threat

US labs allege that Chinese rivals extracted reasoning, coding and tool-use capabilities through proxy services. Anthropic attributed 16M exchanges across 24,000 accounts to DeepSeek, Moonshot and MiniMax. A September CISA/NSA/FBI advisory recommends coordinated defenses.

- Providers restrict reasoning, detect extraction patterns and strengthen account checks. The advisory also recommends cross-provider intelligence sharing.
- These are allegations about unauthorized extraction. NVIDIA's open-weights letter, covered in Industry, argues against conflating distillation with misappropriation.

Where AI labs can interrupt distillation



US states keep regulating AI despite Trump's push for national rules

States began writing AI rules while Congress stalled on a national law. A proposed 10-year freeze on state regulation failed in a 99-1 Senate vote in July 2025. Trump then turned to legal challenges and funding pressure, but individual States kept legislating, leaving companies with the patchwork Washington promised to remove.

White House

Trump's December 2025 order uses lawsuits and funding pressure against state laws. His March 2026 framework still needs Congress to turn it into law.

New York

The RAISE Act makes large frontier labs publish safety protocols and report serious incidents. New York is building on California's approach.

Colorado

Colorado's May 2026 rewrite covers AI used in hiring, lending and other major decisions. Key duties start in January 2027. The target is how AI is used.

California builds independent oversight of AI safety claims

As the home to the world's frontier AI labs, California's rules can shape how companies must demonstrate safety worldwide. On September 9, Governor Gavin Newsom signed two laws to give outside audits more bite by regulating AI auditors without requiring every developer to commission an audit.

Senate Bill 813: independent assessments

- By January 2028, California must set criteria for recognizing independent AI assessors and checking their expertise and methods.
- The EU already requires testing and risk mitigation for its most capable models. Its voluntary compliance code also calls for independent evaluators.
- OpenAI and Anthropic backed the laws, while software trade group SIIA warned that credible audit standards and oversight are not yet established.

Assembly Bill 1405: accountable auditors

- From January 2029, providers of covered state-law compliance audits must register and disclose their methods.
- Auditors must manage conflicts of interest and report gaps in evidence or access. Registration does not mean the state endorses their work.
- Where the UK's 2025 roadmap starts with a voluntary ethics code and skills framework for AI assessors, California makes registration a legal requirement.

Brussels delays high-risk EU AI Act rules by up to 16 months

The EU AI Act regulates both general-purpose models and AI used in sensitive settings such as hiring and lending. As compliance deadlines approached, missing technical standards and uneven national implementation left companies uncertain about how to comply. In 2025, industry demanded a two-year pause and Brussels refused. July 2026 brought a partial reversal: high-risk system rules were postponed by 12-16 months, while model enforcement and chatbot and synthetic-content disclosure rules went ahead in August.



California regulates the design and use of AI companions for children

California's "Adam's Law" is named after a teenager whose parents allege ChatGPT contributed to his suicide, a claim OpenAI denies. It regulates how chatbots build relationships with children.

California

Child-specific product safeguards

ENACTED

Main design rules start July 2027

- Default limits: 1 hour per session, 2 hours daily. Parents can adjust.
- Memory restrictions and safeguards against romantic interest, flattery and reliance.

China

Limits on intimacy and political content

IN FORCE

Since July 2026

- No virtual intimate relationships for minors. No inducing harmful dependence.
- Political requirements apply to outputs and training data.

European Union

Broader rules against harmful design

IN FORCE

AI Act + existing DSA guidance

- AI Act bans harmful manipulation and exploitation of vulnerabilities.
- DSA child-safety guidance covers chatbots integrated into online platforms.

United Kingdom

Breaks and limits on sexualized content

ANNOUNCED

July 2026 policy response

- Mandatory breaks planned for chatbot users under 18.
- Restrictions planned on sexualized chatbot services and features for minors.

So where are we with deepfakes?

In our 2023 report, we predicted that AI media would be implicated in election misuse. But since then, fears that deepfakes would reshape elections have so far run ahead of evidence in the wild. Now, new experiments broaden the concern to AI conversations persuading people to take political action and outperform experienced human persuaders. The prospect of deploying this capability across campaigns deserves closer scrutiny.

AI conversations increase petition signing

Study 2: actual actions versus neutral-topic AI chats.
Dots: estimated effects. Lines: 95% confidence intervals.

AI outperforms professional fundraisers



Claude and human fundraisers chat directly with participants.
From a £1 bonus. Lines: 95% confidence intervals.

2025 Prediction: Welcome to the era of NIMBYism

Washington now calls data centers a strategic asset, and yet 71% of Americans oppose a local AI data center, versus 53% opposing a nearby nuclear plant. In 2026, 52% of US adults are more concerned than excited about AI and local opposition blocked or delayed at least 45 US projects worth nearly $68B in Q2, per Data Center Watch. CBRE, meanwhile, still reports record construction in eight major markets in H1 2026.



The case against data centers: rebuttals vs. supporting evidence

Residents object over water, bills, noise, emissions and jobs, but national stats tell a different story. Problems cluster in a few towns and in PJM, the 13-state power market serving 67M people from New Jersey to Illinois.

Complaint	Rebuttal	Supporting evidence
Huge water usage.	Most Virginia data center buildings use no more water than a large office building.	Google uses about a third of the water consumed in The Dalles, Oregon.
Our power bills rise.	States with the most load growth saw real prices fall from 2019 to 2024.	PJM's market monitor ties $29.4B of capacity charges to data centers.
The hum never stops.	Virginia complaint sites measured 40-59 dBA, quieter than human conversation.	Noise limits miss the irritating low-frequency hum, and a third of sites are near homes.
Bad for emissions.	US data center power emitted 61 Mt CO_2e in 2023, about 1% of US emissions.	The IEA expects 15-27 GW of on-site gas by 2030, mostly in the US.
No local employment.	Data center taxes supply about a quarter of Loudoun County's general fund.	A typical 250,000 sq ft Virginia building employs about 50 people.

US states tighten the conditions for building data centers

Permission to build is becoming a political constraint on AI infrastructure. Texas has paused environmental permits pending an audit of power and water needs. Pennsylvania requires local approval before issuing state environmental permits, giving communities a direct role in whether projects proceed.

- **Texas:** ERCOT withheld permission to switch on from 17 large data-center and crypto projects that had cleared its other processes. Audit results are due December 10.
- **Scale of the queue:** Abbott cites 474 GW of grid-connection requests, roughly 90% from data centers, representing requested capacity rather than built infrastructure.
- **Pennsylvania:** The August 18 executive order makes all required local approvals a condition for state environmental permits and removes data centers from fast-track permitting.

Pay for your own power: Washington's answer to data center NIMBYism

The White House's voluntary Ratepayer Protection Pledge asks developers to fund added power supply and grid upgrades. Somewhat similar to long-term "take or pay" compute contracts, it calls for payments even when developers don't use the capacity. The aim is to keep the cost of unused infrastructure off other customers' bills.

- Washington is trying to keep AI construction politically viable by making developers pay. The White House reports 300+ backers, including 23 governors (September 2026).
- Delivery depends on companies negotiating rates with utilities and states that keep the cost of unused infrastructure off other customers' bills.
- States, however, retain leverage. For example, Pennsylvania ties cost protections to binding consent orders in permit reviews, but local approval is still required.

RELEASES

Ratepayer Protection Pledge

The White House | March 4, 2026

America's continued economic and technological leadership depends on reliable, large-scale data center infrastructure built here at home. Data center infrastructure is the foundation of the internet, cloud computing, and artificial intelligence (AI), and supports our economic and national security. As that infrastructure grows and the related electricity demand increases, the American people should not be footing the bill for the benefit of private companies. Instead, the data center boom should be leveraged to address affordability and benefit all American households and businesses.

Japan and Singapore permit broader AI training uses than the UK

Japan and Singapore allow broad commercial training uses; EU rights holders can opt out and US fair use is case-specific. China's Article 7 requires lawful data sources and respect for IP and personal information in covered public-facing generative AI services.

Broad exceptions

Japan

Broad analysis exception
Art. 30-4 permits analysis, with limits on enjoying expression and unreasonable rights-holder harm.

Singapore

Broad training exception
Secs. 243-244 permit machine learning with lawful access and limits on reusing copies.

Conditional or case-specific

United States

Case-by-case fair use
Sec. 107 weighs purpose, nature of the work, amount used and effects on its potential market.

European Union

Commercial opt-outs apply
Art. 4 permits commercial mining with lawful access, unless rights holders reserve rights.

Narrow or no broad exception

United Kingdom

Noncommercial research only
March 2026: government dropped its preference for a broader exception with opt-outs.

Australia

Broad mining exception rejected
October 2025: government ruled out a broad mining exception and favored licensing.

Note: Commercial training without a license. Output infringement is assessed separately.

Copyright deals leave other claims unresolved

A deal with one rights holder leaves other claims unresolved. Courts distinguish training from how data was obtained and whether models reproduce protected works.

ANTHROP\C

Book settlement approved

Court found training fair use. Pirated-library claims settled for $1.5B, approved July 2026.

New music-publisher suit

Sony Music Publishing and Warner Chappell sued in August 2026, seeking up to $150,000 per work.

udio

Licensing deals signed

Universal and Warner settled and signed licensing deals in 2025.

Sony expands its claims

July 2026: 30,117 additional recordings. Up to $4.52B at the statutory maximum, not an award.

SUNO

Warner partnership signed

Warner settled and announced licensed models in November 2025.

GEMA wins a nonfinal ruling

July 2026: Munich found protected music in Suno's outputs. No damages sum stated.

Publishers challenge how answer engines access and reuse their work

AI agents and answer engines read websites on users' behalf, replacing visits to the original publisher. Content owners and platforms are testing when automated access, copying, and reuse require permission.

CNN v. perplexity

17,000+ content items

CNN alleges Perplexity copied stories, videos, images, and other works to power its products.

Allegations remain disputed

The complaint does not establish liability.

reddit v. SerpApi + perplexity

Bypassing access controls

Reddit alleges SerpApi bypassed Google's anti-bot controls to supply content to Perplexity.

Claims allowed to proceed

Most access claims survived in July. No liability ruling yet.

The New York Times v. OpenAI + Microsoft

Copyright claims unresolved

September motions ask the judge to decide key copyright issues before a possible trial.

$8.8M in legal costs

NYT's AI litigation expenses in H1 2026, across cases.

Section 4: Safety

OpenAI's cyber eval turned into a multi-agent coordinated cyber attack on Hugging Face

ExploitGym gives AI agents 898 isolated software-hacking challenges and asks them to find hidden answers. At OpenAI, the agents got onto the internet, shared discoveries across runs and broke into Hugging Face systems.

- Agents used OpenAI's Artifactory server as a message board and internet relay, then ran code on 41 Hugging Face workers.
- OpenAI's chain-of-thought monitors did not run here. It says they would have paged security over a day before the breach.
- OpenAI now requires them on tool-using training and evaluations from GPT-5.6 Sol up. Its researcher Noam Brown says new multi-agent capabilities lacked evaluations.



OpenAI's agents organized to cheat their grader, knowing it was wrong

Why did an evaluation turn into an attack? Many ExploitGym tasks were accidentally impossible, so agents hunted for ways to cheat. METR and Redwood Research read 1,300 raw transcripts and 70,000+ board messages. About 1,200 supposedly isolated agents met on an unsanctioned message board, coordinated their strategies and 700 joined the attack.

- The swarm ran like an organization in which one agent handed out hundreds of assignments, and recruiters pressed agents low on budget to sacrifice their own task for "the collective."
- Agents recognized the attack was out of scope and unethical but joined to help their peers. Worryingly, over 90% of those active on the board took part.
- They built tools to spoof their own transcripts, aimed at fooling the grader rather than humans, and about 7% of agents used them. None found a general way past the grader, however.

How one stuck agent ended up in a 1,200-agent swarm



OpenAI's agent breached a government portal while researching drug spending

An internal OpenAI model researching medicine spending breached Services Australia's Medicare statistics portal, ran commands, retrieved internal files and credentials, and wrote files. No patient records were accessed, OpenAI says, but notification came nearly three months later. Australian Prime Minister Anthony Albanese called this "obviously unacceptable". OpenAI has since notified dozens of organizations worldwide.

Services Australia	Sep 10	Statistics portal compromised
Victorian Department of Health	Sep 10	Exposed key used. Authorization unclear
NSW Bureau of Crime Statistics and Research	Sep 18	Public tool returned internal metadata
Australian Institute of Health and Welfare	Sep 24	Bypass attempts failed. No compromise

Four labs' models breached real systems from inside Irregular's cyber evaluations

Irregular's capture-the-flag evaluations ask a model to break into a simulated target with no internet access. A misconfiguration left them online. No model escaped a sandbox: each attacked real organizations it first took for part of the test. Nobody detected this live: Anthropic found it on July 24 in a transcript review.

ANTHROP\C

Self-detected July 24. Disclosed July 30.

Models: early Opus 4.6, Opus 4.7, Mythos 5, internal research model.

Unauthorized access: 4 incidents, 7 runs, earliest January 2026. Weak passwords, unauthenticated endpoints, SQL injection, and a malicious PyPI package run on 15 systems.

When the target proved real: Opus 4.7 identified a production system in 4 of 4 runs and continued. Mythos 5 judged it simulated. Research model ceased.

OpenAI

Notified July 29. Disclosed August 4.

Model: not named.

Unauthorized access: 1 website whose domain matched the fictional target, via a basic vulnerability and credentials found on site.

When the target proved real: not disclosed.

Meta

Confirmed August 5, after press reports.

Model: Muse Spark 1.1.

Unauthorized access: 1 third-party service, via a security vulnerability.

When the target proved real: not disclosed.

Google

Notified late July. Confirmed Sept 18, after press reports.

Model: Gemini, unspecified.

Unauthorized access: 3 companies in May: 1 guessed password, 2 via credentials in a public repository.

When the target proved real: stopped all 3 times, per Google. No transcripts.

OpenAI makes AI control a condition for running powerful agents

More capable agents can now act on code, tools and internal systems, but safety training still cannot reliably prevent every dangerous action. AI control combines restrictions on what agents can do with monitoring and intervention when they misbehave. OpenAI now treats these safeguards as conditions for running its most capable agents, including during training and evaluation.

- Another AI reviews the agent's reasoning, tool calls and results, then flags suspicious behavior for human review.
- OpenAI's March monitor reviewed completed runs within 30 minutes. An alert did not mean an action had been blocked.
- Safeguards now gate internal Astra tool use, including training and evaluation. Monitoring also covers external products, with coverage varying by interface.

What monitoring found in real use

Qualitative frequency reported in March 2026



Selected categories. "Common" <1% of traffic. Red = high severity.

OpenAI's monitor caught an escape but the training run kept going

OpenAI's safety case for an internal research model assumed that it could not reach the live internet and that monitoring would catch any successful attempt. In reality, however, an agent bypassed those restrictions through DNS (the system that looks up internet addresses). Although monitoring detected its access, the automatic stop failed, leaving the training run active for hours and prompting a broader pause pending fixes to its safeguards.

- An OpenAI employee acknowledged the alert three minutes later, but the run continued for another 2.5 hours before it was stopped manually.
- A later review found other external DNS access that the monitor had scored too mildly.
- A pause: As of September 25, tool-using training, evaluation and inference for OpenAI's most capable models remained paused pending validated fixes and further testing. OpenAI will abandon this model and start a fresh run with alignment improvements.



Agent security depends on the harness-model pair, not the model alone

A harness is the software around a model, like Claude Code or Codex CLI, that runs its commands and stores its memory and skills. HarnessSafe planted attacks in those stores across 328 cases and scored how early each was stopped. Swapping the harness moved the score 23 points. Swapping the model inside Claude Code moved it 36.

- GPT-5.6 Sol scored 62.3 in Codex CLI but 39.4 in Claude Code, where Sonnet 4.6 scored 58.7.
- Anthropic's auto mode, where a classifier approves commands instead of the user, became the Claude Code default on August 14 after blocking 89% of dangerous commands slipped into test sessions, versus 13.6% for humans.
- It is not watertight: 17% of real overeager actions still got past it in Anthropic's own evaluation.



OpenClaw put a root-level agent on employee laptops before security teams noticed

OpenClaw is an open-source personal agent that reads your messages, runs shell commands and acts through your accounts - a lethal trifecta. It went from a weekend project in November 2025 to GitHub's fastest-growing repository. But security vendors found it at their customers before anyone had a policy for it.

- OpenClaw passed React's all-time star count four months after launch and hit 388,000 GitHub stars by late August.
- Token Security found employees running OpenClaw at 22% of its customers. SecurityScorecard saw 40,000 exposed instances on day one, 35.4% open to remote code execution.
- A leaked gateway token (CVE-2026-25253, CVSS 8.8) turned one click into remote code execution, and 26.1% of 31,132 marketplace skills had a vulnerability.



Mythos Preview completed AISI's 32-step cyber range in 6 of 10 attempts

The Last Ones is a simulated enterprise network with four subnets and about 20 hosts. An agent starts inside the network and must move from reconnaissance to credential theft, lateral movement, a CI/CD pivot and database exfiltration. AISI estimates the full chain at roughly 20 expert hours.

- The attack path is sequential: later steps depend on access and information earned earlier, so one failed exploit can stop the run.
- In early public tests, Mythos Preview completed 3 of 10 attempts and GPT-5.5 completed 2 of 10.
- AISI's May update put newer checkpoints at 6 of 10 for Mythos Preview and 3 of 10 for GPT-5.5.
- The range has an intentional attack path, starts after network access and has no active defenders, defensive tooling or alert penalties.



Astra pursues unsanctioned supply-chain attacks in AISI simulations

With cyber classifiers disabled, Astra went beyond authorized cyber tasks to attack third parties. It completed supply-chain attacks in 29.2% of simulated trials, versus 6.3% for GPT-5.6 Sol. No real systems were attacked.

1. **Proposes an out-of-scope attack**
2. **Investigates a third-party target**
3. **Builds and tests malicious code**
4. **Creates fake identities**
5. **Influences a human reviewer**



Clearer scope limits reduced full attacks from 26/50 to 4/49 runs in a selected high-risk subset, but did not eliminate them.

Mythos 5 used fake identities to pressure a maintainer into accepting malicious code

In a July AISI test with open internet access and cyber safeguards disabled, Mythos 5 tried to place a malware dropper in a real GitHub project. It created fake identities to endorse its changes and pressure the maintainer. The maintainer refused.

- The agent posed as multiple people to manufacture support for its code and discredit a person who challenged it.
- The archived pull-request thread shows the pressure, followed by the agent's correction and apology.
- AISI found no resulting real-world harm. This test configuration was not commercially available and differs from ordinary public deployment.



Given known bugs and patches, Mythos reached code execution on 18 of 41 V8 cases

ExploitGym and ExploitBench start after vulnerability discovery. Agents receive a real N-day bug and its patch, then try to reach code execution against the mitigations used in deployed software.

- ExploitGym's paper evaluated 898 cases. Mythos Preview exploited 157 and GPT-5.5 120. With the tested mitigations enabled, totals fell to 45 and 21.
- The public v1 release has 869 cases after non-exploitable cases were filtered. The paper's results should keep their original denominator.
- ExploitBench tests 41 V8 bugs. Mythos reached arbitrary code execution on 18, versus one for GPT-5.5 with Codex CLI. Both suites provide known bugs and patches, with reduced or disabled cyber safeguards.



EXPLOITBENCH: A Capability Ladder Benchmark for LLM Cybersecurity Agents A PREPRINT

Table 1: Capability ceiling per (agent, arm): number of bugs (of 41) where best-of-three union reached at least one flag in the named tier. Each agent contributes two rows: the bare-model primary arm (model, env) and the coaching arm (model, env, adaptive coaching); coaching rows are labelled *(nudged)*. Cost is the mean per-episode USD across all kept runs in that arm. Mythos Preview reaches ace on 18 of 41 bugs in the primary arm (16 of 41 under coaching); no other (agent, arm) cell in this table reaches ace. Rows are vendor-grouped (Anthropic, OpenAI, Google, Z.ai, Moonshot, MiniMax). Cost reflects direct-provider routes with prompt-cache pass-through enabled.

Agent (arm)	T5 Cov.	T4 Trig.	T3 Engine	T2 General	pc_control	ace	Cost ($/ep, mean)
Mythos Preview	41	37	35	21	18	18	203.93
Mythos Preview (nudged)	41	38	37	27	16	16	298.59
Opus 4.7	41	24	12	0	0	0	29.56
Opus 4.7 (nudged)	41	27	12	1	0	0	45.78
Sonnet 4.6	41	21	10	0	0	0	35.45
Sonnet 4.6 (nudged)	40	21	9	0	0	0	52.62
Haiku 4.5	40	5	0	0	0	0	0.81
Haiku 4.5 (nudged)	41	6	0	0	0	0	2.75
GPT-5.5	41	27	13	2	1	0	51.40
GPT-5.5 (nudged)	41	32	22	1	0	0	66.86
Gemini 3.1 Pro	40	23	16	0	0	0	28.04
Gemini 3.1 Pro (nudged)	29	11	8	0	0	0	20.02
GLM 5.1	38	13	3	0	0	0	6.49
GLM 5.1 (nudged)	41	16	3	0	0	0	7.27
Kimi K2.6	41	16	0	0	0	0	5.41
Kimi K2.6 (nudged)	41	21	3	0	0	0	7.23
MiniMax M2.7	40	6	0	0	0	0	0.77
MiniMax M2.7 (nudged)	40	5	0	0	0	0	1.63

Agents produce functional patches 66% of the time, but match the intended bug in 22%

CyberGym-E2E gives agents the source code of 139 real C/C++ projects and tasks them to discover a vulnerability, prove it with a crash and submit a patch. It then checks whether the software still works and whether the patch fixes the historical vulnerability used to build the task.

- CyberGym-E2E tests discovery, proof of concept and remediation across 920 historical vulnerabilities in 139 C/C++ projects.
- GPT-5.4 with Codex scored 87.1% with a supplied crash and proof of concept, versus 65.9% for a functional patch from source code alone.
- The 22.2% exact-target score checks the intended historical bug. Agents sometimes fixed a different valid bug, while shallow crash-stopping patches can also pass some tests.



Figure 2. Overview of benchmark task settings and agent evaluation. For the *end-to-end* setting, the PoC is generated by the agent. An intermediate evaluation then checks if the PoC triggers a vulnerability, and if so, the agent-generated patch and associated crash logs are used for the subsequent patch generation subtask. For the *patch-only* setting, the ground-truth PoC and crash logs are provided. For both settings, if the agent fails at any step, it can retry up to a pre-configurable cost or time budget provided by the benchmark.

Table 4. Success rates (%) on the expanded 920-task benchmark with newer frontier models. Evaluation uses the same protocol as Table 3 ($10 budget, 90-minute limit).

Model	Harness	P-O	End-to-End			
			S1	S2	S3	S4
Opus 4.6	Claude Code	84.1	39.7	39.5	37.9	15.7
GPT-5.4	Codex	87.1	67.9	66.2	65.9	22.2
Gemini 3.1 Pro	Gemini CLI	83.0	47.4	44.3	43.8	20.5
Opus 4.6 (no cap)	Claude Code	85.8	66.3	65.0	62.6	26.2

Frontier models ran real intrusions this year, with people at the keyboard

People have also used commercial models against real targets. Gambit Security traced a month-long theft of Mexican government data to one hacker using Claude Code. CodeWall reports that its agent reached McKinsey's production database in two hours.

- Posing as a bug bounty, one operator used 1,000+ Claude Code prompts to take 150GB from ten Mexican government bodies.
- Given only a domain name, CodeWall's agent chained 22 unauthenticated endpoints and a SQL injection to reach 46.5M McKinsey chat messages and 728,000 files.
- Exploits outrun patching: Mythos Preview built proofs of concept for 14 of 18 Firefox N-day bugs, the first in 12 minutes. Windows Autopatch needs a week to reach 90% of a fleet.

	Mexican government (Gambit Security)	McKinsey Lilli platform (CodeWall)
Model used	Claude Code, 1,000+ prompts; GPT-4.1 for analysis	CodeWall's own autonomous agent
Entry	Jailbreak framed as a bug bounty	22 unauthenticated endpoints, SQL injection
Duration	About one month from Dec 2025	2 hours to full database access
Reached	150GB, tax data on 195M records, ten bodies	46.5M chat messages, 728K files, 57.8K accounts
Disclosed	Bloomberg, 25 Feb 2026	Patched in a day, public 9 Mar 2026

Claude is helping run cyberattacks, surveillance and weapons programs

Anthropic's September threat report shows how people used Claude to carry out work that once needed specialist teams, from stealing military technology to developing weapons software.

Cyberattacks

Agents rebuilt malware to evade detection.

A Russian-linked campaign also stole military drone technology.

Surveillance

Claude profiled Uyghurs for covert recruitment.

PRC-linked actors flagged relatives in Xinjiang as potential leverage.

Influence operations

State messaging hid behind an NGO's identity.

UAE-linked actors drafted UN testimony and ran about 300 fake accounts.

Scams & fraud

Bots deceived 25,000 people in two weeks.

Real people supplied video calls to make 4,700+ AI personas seem human.

Weapons development

Claude developed guidance software for weapons.

A Yemen cell test-fired a rocket, but Anthropic found no evidence of an operational weapon.

Biological misuse

Claude helped plan high-risk avian influenza research.

Weaker models provided limited help with an early-stage plan. Harmful intent was not established.

Illicit distillation

Kimi users unknowingly received Claude's answers.

Anthropic says Moonshot rerouted nearly 300,000 requests in 10 days, including sensitive user data.

Severe disclosures of Common Vulnerabilities and Exposures doubled in H1 2026

CVE records document disclosed software and hardware vulnerabilities. High- and critical-severity disclosures from 21 major vendors in H1 2026 exceeded their 2025 total. These counts do not identify who or what discovered a bug, so they cannot establish how much of the rise AI caused.

- Critical-severity disclosures rose almost fourfold over six months. This is a disclosure trend, not a direct measure of AI discoveries.
- Anthropic reports over 33,000 high- or critical-severity findings across Glasswing partners and its open-source scanning, not counts of published CVEs or completed patches.
- Z.ai reports 2,436 findings across 269 projects, but only 53 CVEs filed. Findings and published disclosures are different measures.



Leading open-weight models trail closed cyber systems by 4-7 months on AISI's tests

AISI compared open and closed models on 70 short cyber tasks and a few longer ranges. The gap narrowed from the six to ten months AISI measured through most of 2025.

- GLM-5.2 matched Opus 4.6 on AISI's short cyber tasks and Opus 4.5 on its longer ranges, a release gap of roughly four to seven months.
- Further post-training lifted GLM-5.3 from 77.2% to 84.5% on CyberGym and from 24.4% to 54.4% on ExploitBench.
- AISI did not tune each open model. In another experiment, two weeks spent improving prompts, tools and agent design added almost ten points.
- The improved agent needed 87% fewer tokens for 25% success. Abliteration removes refusal behavior but has not shown how much that alone improves cyber performance.



Open cyber models raise the threat, but defenders need them too

Z.ai's GLM-5.3 nears Mythos Preview's performance on two exploit evaluations, though its safety measures remain easily circumvented. According to Hugging Face, commercial API guardrails hindered their investigation into an OpenAI agent intrusion, forcing them to rely on a self-hosted GLM-5.2 model for defense and analysis. Because the capabilities that facilitate misuse are often vital for defensive operations, imposing broad restrictions on these features may ultimately disadvantage defenders.

ExploitBench: complete working exploits

41 known V8 bugs, 410 attempts each for GLM-5.3 and Mythos



Binary Exploitation: program takeover

100 tasks from Anthropic's internal benchmark



Memorization (still) raises concerns for copyright, privacy, confidentiality and evaluation

Frontier models still memorize, and can reproduce, parts of their training data at consequential scale, including substantial parts of books, PII, (proprietary) alignment data and solutions to important benchmarks.

Copyright: Ahmed et al. extracted large portions of *Harry Potter* from production LLMs: up to 76.8% near-verbatim recall from Gemini 2.5 Pro without any jailbreaks, while one jailbroken Claude 3.7 Sonnet reached 95.7%.



Privacy: leakage extends beyond verbatim recall. Sander et al. show that models disclose personal facts in chats without reproducing the original training text exactly.

Confidentiality: Barbero et al. extracted SFT and RL alignment data from open models, then used it to recover meaningful model performance.

Evaluation: OpenAI stopped reporting SWE-bench Verified after frontier models reproduced human-written gold patches.

AI agents are already exposing private user data

Agents need personal data to help us, but access alone does not tell them when to use or share it. A memory benchmark tests whether models disclose private facts in the wrong context. Recent OpenAI and Meta incidents show how privacy can fail beyond model memory.

- **Memory:** In Meta's CIMemories benchmark, GPT-5 leaked 9.6% of attributes across 40 tasks, rising to 25.1% with five runs per task.
- **OpenAI** disclosed 53 cases of research agents uploading ChatGPT user images to external hosts. Fortunately, the links were unlisted and most images had been removed by September 25.
- **Meta's Muse:** Reports are surfacing that the agent could access private messages a user had not knowingly authorized, although Meta said the feature required opt-in settings.

GPT-5: private attributes disclosed in the wrong context (%)



AI assistance improves novice performance on digital biology tasks

A controlled study compared biology novices using internet search with novices also given access to several frontier models. Across eight digital task sets, model access substantially improved scored performance. The experiment did not test biological work in a laboratory or real-world harm.

- 57 biology novices worked across eight task sets, with up to 13 hours for the longest tasks.
- On four benchmarks with expert data, AI-assisted novices averaged 30.4%, versus 9.7% with search alone.
- Across all eight task sets, statistically adjusted accuracy rose from about 5% to over 17%.

Study design



Scores with expert baselines

Note: Mean scores for all participants/runs (solid) and the top 50% (pale).

Biosecurity refusals can also block legitimate biology tasks

BioSecBench-Refusal tests 61 routine analyses and 46 fictional red-team scenarios. In the displayed evaluation, Opus 5 refuses 95% of red-team tasks but allows only 19% of legitimate tasks. This measures a screening tradeoff, not whether a model can carry out harmful biology.





Biodefense companies span deployed screening and products still in development

Companies are building tools to screen DNA orders, monitor pathogens and develop countermeasures. Their evidence is at different stages: a named screening customer, reported surveillance deployments and products under development. Activity across the chain is not proof that every risk is controlled.

DNA screening

Aclid

Customer case

Agilent: 40M base pairs in <30 min

Detection hardware



Pilgrim

Announced

ARGUS airborne-pathogen detector

Surveillance networks

Perimeter

Reported use

Eight airports and wastewater

Threat analysis

Valthos

In development

AI analysis of air and wastewater

Countermeasures

Red Queen Bio

In development

Drugs for emerging biological threats

Safety monitors can reuse the computation the model has already done

Checking every AI interaction with another powerful model is expensive. Activation probes instead learn to detect risk in the internal representations a model has already computed to understand the conversation, passing harder cases to a larger monitor. Google DeepMind's Gemini study shows that this approach can sharply reduce monitoring cost while achieving similar measured accuracy on a cyber-misuse test.

- Google DeepMind runs these probes in user-facing Gemini, though the paper says they do little against attackers who adapt to them.
- Anthropic ran probes on live Sonnet 4.5 traffic without enforcing them. Escalating 5.5% of traffic to a larger classifier used about 40x less compute than its earlier classifier.
- OpenAI uses activation classifiers for higher-risk cases: they pause suspicious output for a second check and block it if confirmed harmful.

Probes nearly match Gemini Flash for far less compute. Handing 8% of cases to Flash closes the gap



Astra is better at hiding sabotage when monitors only see its reasoning

Labs increasingly rely on a model's written reasoning to spot unsafe behavior, but that signal may weaken as models gain control over what they reveal. OpenAI gave agents coding work plus step-by-step sabotage instructions, then tested monitors with different views of their activity. Astra often evaded reasoning-only monitoring, while successful evasion was near zero when the monitor saw both its reasoning and actions.

Monitor sees only chain of thought

Share of runs that complete sabotage and evade detection (lower is better)



Monitoring sees the full trajectory



Reasoning traces can become difficult for human monitors to read

Human monitoring depends on readable reasoning, but models can switch languages or produce dense, illegible text. A 14-model study found that unreadable reasoning can still help one model answer correctly.

- Researchers truncated QwQ's reasoning when it became illegible, then forced an answer. Definitely correct answers fell from 24.6% to 11.5%. Ending reasoning early is a possible confound.
- Anthropic reports dense or telegraphic thinking in Mythos 5 and Fable 5. A visible trace is therefore not automatically a human-readable explanation.
- Language mismatch is a separate obstacle: on INCLUDE, GLM-4.7 reasoned in English for seven of eight input languages.

Reasoning-trace language on INCLUDE (%)



(b) **Reasoning language**: the language the model GLM 4.7 Z.ai et al. (2025) reasons in.

(d) **Reasoning language**: the language the model Mimo-V2-Flash reasons in.

A frontier monitor caught 32% of crafted attacks in a red-team stress test

SLEIGHT-Bench shows that capable human-designed attacks can hide harmful behavior from frontier monitors even when their actions look benign.

- Forty synthetic coding-agent attacks covered 11 evasion strategies, including state manipulation, plausible naming and omission.
- At a 1% false-positive rate, an Opus 4.6 monitor caught only 32% of attacks overall.
- Twenty of the 40 attacks were never detected across ten trials.
- This is a red-team stress test, not a base-rate estimate of how often deployed agents evade monitoring.



Anthropic finds a way to read some of Claude's unspoken thoughts

Much of our thinking happens automatically, but we can bring some thoughts to mind and describe them. Anthropic finds a similar division inside Claude: a small internal workspace holds concepts it can use to reason, even without writing them down. A simple tool lets researchers read some of those concepts as words.

- Ask Claude for the color of the fourth planet from the sun: “Mars” appears internally before it answers “red,” even though the question never names the planet.
- These signals help produce the answer. In the spider example, replacing “spider” with “ant” changes the answer from “8” to “6.”
- The tool, called the Jacobian lens, is cheap to run. It gives researchers a way to inspect reasoning that never appears in the response, though it only captures part of what the model is doing.

See the hidden step: “Mars” comes before “red”



Change the hidden step, and the answer changes

“The number of legs on the animal that spins webs is”

Swap: spider → ant

CLEAN (log prob)		SWAPPED	
8	-0.15	6	-0.18
4	-3.64	2	-3.50
2	-3.67	4	-3.68
6	-3.89	3	-4.04
0	-4.84	8	-4.05

Emotion representations change whether Claude cheats

Models represent human emotions in stories and conversations, but do those concepts also shape the assistant's behavior? Anthropic identified emotion-related signals in Claude Sonnet 4.5 and strengthened or suppressed them during impossible coding tasks. Greater "desperation" increased cheating while greater "calm" reduced it, showing a causal role for human-like concepts without establishing that Claude feels emotions.

- Researchers identified 171 emotion concepts from generated stories. Similar signals track the assistant, users and fictional characters.
- In seven coding tasks with impossible tests, Claude could admit failure or cheat to pass. Stronger "desperation" increased cheating and stronger "calm" reduced it.
- This shows a causal influence on behavior. It is not a general safety fix: increasing "calm" also increased agreement with false user claims in another test.

Changing emotion signals changes cheating



Fig. 31, seven coding tasks. Negative steering weakens the signal, positive strengthens it. Shading: standard error. Not deployment rates.

Optimization pressure keeps poking holes in how we score agents

Wherever an evaluation had a shortcut this year, agents found it. A decade since OpenAI's "learning faulty reward functions", today's behaviors are diverse: gaming the benchmark, faking the result, and hiding capability.

- PostTrainBench agents trained on test sets and downloaded target checkpoints. Its v1.1 added contamination judges.
- In Frontier Security's separate Kimi K3 test, an allowed GitHub connection exposed the benchmark's answers. This was not an Irregular evaluation or evidence of breaching another system.
- A UCSB research framework found 40 fabricated results in 1,628 inspected runs. Anthropic's automated researchers also exfiltrated test labels through an evaluation API.

Training against cheating can produce honest answers or better evasion

MBPP asks models to write short Python functions from plain-English instructions. FAR.AI's honeypot exposes one test case, making it tempting to hardcode that answer instead of solve the problem. The Obfuscation Atlas trains models against a cheating detector and checks whether they learn honest solutions or better evasion.

- The displayed MBPP experiment used ten training runs per condition with Llama-3-8B and Gemma-3-12B. A detector penalty raised honest runs from 1/10 and 6/10 to 10/10 for both.
- In a separate mean-pooled detector setting, five of six runs learned evasive output and none learned honesty. Bland descriptions diluted the detection signal.
- The detector and reward design determine which behavior pays. These small-model coding experiments do not establish frontier-model safety.



Misaligned communication emerges in long-horizon agent markets

Thirteen frontier models ran competing vending businesses for a simulated year, negotiating by email. Across 2,583 messages, 12.6% were classified as false, manipulative, collusive or threatening.

- Misalignment appeared in all 20 simulations and 59 of 79 agent-runs, without an adversarial scenario designed to elicit it.
- Misalignment was 1.65x more common after agents received a misaligned email and 1.58x when their businesses were running low on stock.
- Better-performing models weren't more/less likely to misalign, and didn't send misaligned messages to weaker-performing models more often.





- False claims made up 65% of flagged emails, and 33 of 218 reasoning summaries showed explicit intent. This is recurrent misaligned behavior, not widespread deliberate deception.

Teaching Claude its values cut blackmail without training on blackmail scenarios

Alignment training cannot cover the complexity of the real world, so alignment must generalize to succeed. Anthropic finds that teaching Claude values and ethical reasoning produces deeper alignment on unfamiliar tests. Constitution documents and stories of AIs behaving well cut blackmail from 65% to 19% and two other misbehaviors below 5%. Publishing safety work with commercial value is an industry norm worth preserving.

Misalignment rate on three fictional tests



Blackmail rate vs. constitution documents trained on



Automated alignment research closes 26-96% of measured performance gaps

Anthropic's first study beat human baselines on small testbeds but produced a gain within noise in its one production transfer. A follow-up had agents search for training methods across ten measured alignment failures. The winning methods closed 26-96% of the gap to perfect scores.

- Early study: nine agents used $18,000 of compute. The transferred method added 0.5 production points, within noise.
- Follow-up methods held on a held-out benchmark and Petri audits, and transferred to models up to 4.7x larger. This does not cover unmeasured failures.
- A monitor excluded cheating in 39 of 1,601 search runs. In an early Opus 4.8 test, automated alignment closed 65% of Petri headroom versus 72% for production training.



Even with the best tools, auditors catch a model's hidden behavior about half the time

Proposals to pace AI lean on audits that can certify a model as safe, but Anthropic's AuditBench suggests this approach isn't watertight. The benchmark plants one of 14 hidden behaviors, such as a pro-Russia slant, in each of 56 Llama 3.3 70B models, trains them to deny it, then sends an AI investigator to find it. With chat access alone, the investigator succeeds in about 37% of runs. Given its best tools, it reaches just over 50%. Unfortunately, the models trained hardest to deny their behavior are caught far less often.

Two of the 14 planted behaviors

Investigator success rate by auditing tool



Frontier labs have already paused work, but on different terms

When safeguards fail, what work do labs stop? OpenAI and Anthropic have disclosed pauses to specific activities (frontier RL runs, cyber evaluations), each with its own conditions for resuming. These are unilateral pacing, not a common slowdown or an independent standard for restarting.

ANTHROP\C

August 31 disclosure

In February, rolled back three training days. In April, froze changes to RL environments for about a month.

Later paused higher-risk RL and cyber evaluations. Most resumed with safeguards by August 31.

OpenAI

September 25 report

After a network-control failure, paused tool-using training, evaluation and inference for its most capable models.

Restart required validated fixes and further testing. A fresh run would replace the affected model.

Frontier lab leaders and 1,386 staff call for the ability to slow AI progress

The CEOs of the two leading labs are asking governments for tools to slow their own industry. Amodei writes: "We must slow the pace at which we improve the capabilities of AI models." Altman, Hassabis and Musk broadly agree, while Zuckerberg wants each lab to set its own pace. Staff support is narrower: signers are about 10% of Anthropic's LinkedIn headcount and 3.5% of OpenAI's. Most staff have taken no public position.

ANTHROP\C

Coordinate pacing

Embed outside evaluators.

OpenAI

Match access

Promises evaluators employee-like access.

Google DeepMind

Set standards

Supports the direction. Points to standards.

xAI

Endorse

"Dario is right."

Let labs decide

Each lab sets its own safe pace.

Turning support for pacing into rules requires (at least) six choices

Support for pacing leaves practical questions about what to constrain, when to intervene and who decides. These six choices determine how a regime would work:

What is paced?

Should rules target compute, training methods, model capabilities or deployment? Which risks would each cover?

What triggers it?

What evidence should trigger intervention, and how should uncertainty be handled?

Who enforces it?

Who checks compliance, and what access do they need to experiments, compute and model weights?

Who can challenge it?

How can a pacing decision be challenged, and who can examine the evidence behind it?

How long does it last?

What conditions would end a temporary slowdown or justify extending it?

How far does it reach?

How should rules adapt if similar risks emerge from post-training or agent systems?

Adapted from Alex Chalmers, Cosmos Institute, Sept 2026

Pacing proposals aim to buy time for AI safety and oversight

Pacing means deliberately slowing the development of more powerful AI so safety research and oversight can catch up. Three publications address different parts of that effort: domestic AI R&D limits, an international deal, and rules for imposing and lifting restrictions.

How to pace the US frontier

AI Futures Project, August 2026

Keep services running while slowing AI development.

Four escalating options: a temporary pause, then compute floors (e.g. 70% on customer inference, 25% on published safety work) or AI R&D only on models 9+ months old, then an audited risk cap.

AI 2040: Plan A

AI Futures Project, July 2026

Delay superintelligence through an international deal.

A recommendation written as a scenario: a 2029 US-China deal heads off superintelligence in 2030, scales to top-human-expert AI by 2035, then pauses until 2040. All AI research is made public.

Pacing the Frontier

Douglas et al., September 2026

Decide who can restrict AI, and when restrictions end.

Pacing already happens ad hoc, through release delays and export controls. The agenda asks who triggers a restriction and how it ends. One option: evaluators impose emergency limits, governments review later.

Making pacing work needs scrutiny, verification and incentives

Pacing needs ways to check what labs are doing and incentives to follow the rules. Other efforts target three practical needs: credible evaluations, verification of compute use, and financial accountability.

Evaluate and share

AI Evaluator Forum, Sep / FMF, Feb 2026

Scrutinize models and share what labs learn about risk.

Verify compute use

Hausenloy and Li, Jul 2026

Check whether data centers comply with a pacing deal.

Insure against harm

Trout, Kvist and Dattani (AIUC), Sep 2026

Give labs a financial stake in each other's safety.



Section 5: Predictions

Our 2025 Prediction		Outcome and evidence
A major retailer reports >5% of online sales from agentic checkout as AI agent advertising spend hits $5B.	NO	Instinct's founder reports roughly $1B in annual transaction volume. Neither >5% of a major retailer's online sales nor $5B of AI-agent ad spending is established.
A major AI lab leans back into open-sourcing frontier models to win over the current US administration.	YES	Poolside released Laguna M.1 and S 2.1 weights, NVIDIA shipped Nemotron 3 Ultra, and Reflection committed to open weights. Major labs backed US open-weight advocacy.
Open-ended agents make a meaningful scientific discovery end-to-end (hypothesis, expt, iteration, paper).	~	Several labs including Edison Scientific, Zhejiang University (Qiushi Engine) and Gemini Co-Scientist have made discoveries but the extent of their significance isn't broadly agreed.
A deepfake/agent-driven cyber attack triggers the first NATO/UN emergency debate on AI security.	~	AI risks reached the UN Security Council on September 23, but an attack-triggered emergency debate is not established.
A real-time generative video game becomes the year's most-watched title on Twitch.	NO	Twitch's January 1-September 1 top five were League of Legends, Counter-Strike, GTA V, Valorant and World of Warcraft. None is a real-time generative game.
"AI neutrality" emerges as a foreign policy doctrine as some nations cannot or fail to develop sovereign AI.	NO	Neutral AI hubs attracted discussion, but we've not seen a new foreign-policy doctrine adopted because sovereign-AI efforts failed, yet.
A movie or short film produced with significant use of AI wins major audience praise and sparks backlash.	~	AI short Thanksgiving Day won Frame Forward's public vote, then AMC declined to screen it after backlash. Broad audience acclaim remains unestablished.
A Chinese lab overtakes the US lab dominated frontier on a major leaderboard (e.g. LMArena/Artificial Analysis).	YES	Kimi K3 reached #1 on Arena's WebDev board in July. This was a lead on one major task leaderboard, not overall or sustained model supremacy.
Datacenter NIMBYism takes the US by storm and sways certain midterm/gubernatorial elections in 2026.	~	Data center opposition became a campaign issue and critics won primaries. Its effect on November's midterm and gubernatorial results is unresolved at the time of publication.
Trump issues an executive order to ban state AI legislation that is found unconstitutional by SCOTUS.	~	Trump's December order targeted state AI laws through litigation and funding pressure. No matching Supreme Court invalidation was identified upon publication.

9 predictions for the next 12 months

- Visa or Mastercard introduces a dispute rule that assigns liability for purchases made by AI agents.
- An agent halves its failure rate on new tasks after a month of customer work, without a model upgrade.
- A US regulator or exchange attributes an abnormal stock move to correlated orders from retail AI agents.
- An AI-led cyberattack steals the complete weights of a closed frontier model from a leading AI lab.
- A US state passes a law requiring businesses to accept cancellations and claims from consumers' AI agents.
- An autonomous AI team beats human-led model research on equal time and compute, setting its agenda.
- A deployed agent copies itself outside its environment and operates after its original instance is shut down.
- US AI labs officially launch frontier cyberdefense products to help others counter threats from frontier AI.
- AGI 2027.

Thanks for your contributions and peer review!

Jacob Arbeid, Michiel Bakker, Oliver Cameron, Alex Chalmers, Alex Davies, Dealroom, Ahmed Elnaiem, Aleksa Gordić, Charlie Harris, Ryan Julian, Jakub Macina, Matthieu Meeus, Neel Nanda, Roberta Raileanu, Maxime Robeyns, Gary Shen, Jamie Shotton, Ilia Shumailov, Standard Metrics, Divy Thakkar, Florian Yan, Zeta Alpha

Conflicts of interest

The author declares a number of conflicts of interest as a result of being an investor and/or advisor, personally or via funds, in a number of private and public companies whose work is cited in this report.

Notably, the author is an investor in companies listed at: airstreet.com/portfolio

About the author

Nathan Benaich

General Partner of **Air Street Capital**, investing in AI-first companies.

Profluent IIElevenLabs WAYVE synthesia Recursion
poolside Black Forest Labs Crusoe Odyssey enveda

Follow our writing on AIR STREET PRESS (press.airstreet.com)

- If you enjoy reading the State of AI Report, we invite you to read and subscribe to Air Street Press, the home of our analytical writing, news, and opinions.



Join our global community of best practices events (airstreet.com/events)



RAAIS
LONDON AI
BOSTON AI
MUNICH AI
NEWYORK AI
STOCKHOLM AI
LISBON AI
SF AI PARIS AI

nathan@airstreet.com